Safety Data Sheet

Loctite 55 24x12m Serbia

SDS No. : 168432
V001.12
Revision: 12.01.2025
printing date: 04.11.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:
Loctite 55 24x12m Serbia

Other means of identification:
Loctite 55 24x12m Serbia

Product code:
IDH1401520

Recommended use of the chemical and restrictions on use

Intended use:
Adhesive

Manufacturer/Importer/Distributor Representative Company

Henkel Thailand Ltd. The Offices at Centralworld,
35th Floor, 999/9 Rama 1 Rd.,
Kwang Patumwan, Khet Patumwan,
10330 Bangkok

Thailand

Phone: +66 (2209) 8000
Fax-no.: +66 (2209) 8008

E-mail address of person responsible for Safety Data Sheet:
ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents:
FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +662 209 8008

Section 2. Hazards identification

GHS Classification:

Substance or mixture is not classified as hazardous according to Globally Harmonized System(GHS).

GHS label elements:

Substance or mixture is not classified as hazardous according to Globally Harmonized System(GHS).

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Limestone 1317-65-3	30- 60 %	
Talc 14807-96-6	1- 10 %	
octamethylcyclotetrasiloxane 556-67-2	< 0.1 %	Flammable liquids 3 H226 Toxic to reproduction 2 H361 Chronic hazards to the aquatic environment 1 H410

Section 4. First aid measures

Inhalation:
Move to fresh air, consult doctor if complaint persists.

Skin contact:
Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:
Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:
Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

Section 5. Fire fighting measures

Suitable extinguishing media:
water, carbon dioxide, foam, powder

Improper extinguishing media:
High pressure waterjet

Specific hazards arising from the chemical:
In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

Special protection equipment and precautions for firefighters:
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional fire fighting advice:
In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:
Wear protective equipment.
Avoid skin and eye contact.
Ensure adequate ventilation.
See advice in section 8

Environmental precautions:
Do not empty into drains / surface water / ground water.

Clean-up methods:
For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:
Avoid skin and eye contact.
Use only in well-ventilated areas.
See advice in section 8

Storage:
Refer to Technical Data Sheet.
Store in a cool, dry place.
Keep container tightly sealed.
Storage at -20 to 50°C is recommended.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

CALCIUM CARBONATE, RESPIRABLE DUST 1317-65-3	**Value type**	Time Weighted Average (TWA):
	mg/m³	5
	Remarks	TH OEL
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles 1317-65-3	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles 1317-65-3	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
Limestone 1317-65-3	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
CALCIUM CARBONATE, INHALABLE DUST 1317-65-3	**Value type**	Time Weighted Average (TWA):
	mg/m³	15
	Remarks	TH OEL
TALC, CONTAINING NO ASBESTOS FIBERS, RESPIRABLE FRACTION 14807-96-6	**Value type**	Time Weighted Average (TWA):
	mg/m³	2
	Remarks	ACGIH The value is for particulate matter containing no asbestos and <1% crystalline silica.
TALC CONTAINING NO ASBESTOS FIBRES, RESPIRABLE DUST 14807-96-6	**Value type**	Time Weighted Average (TWA):
	mg/m³	2
	Remarks	TH OEL

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Body protection:
Suitable protective clothing
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:
Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures:
The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Opaque solid
Odor:	Mineral-oil-like
Odor threshold (CA):	No data available.
pH:	Not applicable, Product is non-polar/aprotic.
Melting point / freezing point:	Not applicable, Determination technically not possible
Specific gravity:	1.25
Boiling point:	> 150 °C (> 302 °F)
Flash point: (Closed cup)	> 93 °C (> 199.4 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure: (; 20 °C (68 °F))	< 0.13 mbar
Vapor density:	Not applicable, Product is a solid
Density:	No data available.
Solubility:	Partially soluble (23 °C)
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	(; 20 °C (68 °F); Method: no method / method unknown) 11,000 cp (; 120 °C (248 °F))
VOC content: (2010/75/EC)	< 3 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials:
None if used for intended purpose.
Chemical stability:
Stable under recommended storage conditions.
Conditions to avoid:
None if used for intended purpose.
Hazardous decomposition products:
No decomposition if used according to specifications.

Section 11. Toxicological information

Symptoms of Overexposure**:** None known.

Acute oral toxicity:

Limestone 1317-65-3	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 420 (Acute Oral Toxicity)
Talc 14807-96-6	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 423 (Acute Oral toxicity)
octamethylcyclotetrasiloxane 556-67-2	Value type	LD50
	Value	> 4,800 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

Limestone 1317-65-3	Value type	LC50
	Value	> 3 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)
Talc 14807-96-6	Value type	LC50
	Value	> 2.1 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)
octamethylcyclotetrasiloxane 556-67-2	Value type	LC50
	Value	36 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)

Acute dermal toxicity:

Limestone 1317-65-3	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Talc 14807-96-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
octamethylcyclotetrasiloxane 556-67-2	Value type	LD50
	Value	> 2,375 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Limestone 1317-65-3	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Talc 14807-96-6	Result	slightly irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
octamethylcyclotetrasiloxane 556-67-2	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Limestone 1317-65-3	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Talc 14807-96-6	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
octamethylcyclotetrasiloxane 556-67-2	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Limestone 1317-65-3	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Talc 14807-96-6	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
octamethylcyclotetrasiloxane 556-67-2	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Limestone 1317-65-3	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Limestone 1317-65-3	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Limestone 1317-65-3	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Talc 14807-96-6	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Talc 14807-96-6	Result	negative
	Type of study / Route of administration	in vitro mammalian cell transformation assay
	Metabolic activation / Exposure time	without
	Method	equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Talc 14807-96-6	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	rat
	Method	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)
octamethylcyclotetrasiloxane 556-67-2	Result	negative
	Type of study / Route of administration	bacterial gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
octamethylcyclotetrasiloxane 556-67-2	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
octamethylcyclotetrasiloxane 556-67-2	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
octamethylcyclotetrasiloxane 556-67-2	Result	negative
	Type of study / Route of administration	inhalation
	Metabolic activation / Exposure time	
	Species	rat
	Method	equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
octamethylcyclotetrasiloxane 556-67-2	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	rat
	Method	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)

Repeated dose toxicity:

Limestone 1317-65-3	Result	NOAEL=1,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	48 ddaily
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Talc 14807-96-6	Result	NOAEL=100 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	101 d7 d/w
	Species	rat
	Method	equivalent or similar to OECD Guideline 452 (Chronic Toxicity Studies)
octamethylcyclotetrasiloxane 556-67-2	Result	LOAEL=35 ppm
	Route of application	inhalation
	Exposure time / Frequency of treatment	6 h nose only inhalation5 days/week for 13 weeks
	Species	rat
	Method	OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)
octamethylcyclotetrasiloxane 556-67-2	Result	NOAEL=960 mg/kg
	Route of application	dermal
	Exposure time / Frequency of treatment	3 w5 d/w
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Toxicity:

Limestone 1317-65-3	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	not specified
Limestone 1317-65-3	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	not specified
Limestone 1317-65-3	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	not specified
Limestone 1317-65-3	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Talc 14807-96-6	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)

	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
octamethylcyclotetrasiloxane 556-67-2	Value type	NOEC
	Value	0.0044 mg/l
	Acute Toxicity Study	Fish
	Exposure time	93 d
	Species	Salmo gairdneri (new name: Oncorhynchus mykiss)
	Method	EPA OPPTS 797.1600 (Fish Early Life Stage Toxicity Test)
	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	EPA OTS 797.1400 (Fish Acute Toxicity Test)
octamethylcyclotetrasiloxane 556-67-2	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
octamethylcyclotetrasiloxane 556-67-2	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
	Value type	EC10
	Value	0.022 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
octamethylcyclotetrasiloxane 556-67-2	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge
	Method	ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)

Persistence and degradability:

octamethylcyclotetrasiloxane 556-67-2	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	3.7 %
	Method	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)

Bioaccumulative potential / Mobility in soil:

Talc 14807-96-6	LogPow	-9.4
	Temperature	25 °C
	Method	QSAR (Quantitative Structure Activity Relationship)
octamethylcyclotetrasiloxane 556-67-2	Bioconcentration factor (BCF)	12,400
	Exposure time	28 d
	Species	Pimephales promelas
	Temperature	
	Method	EPA OTS 797.1520 (Fish Bioconcentration Test-Rainbow Trout)
octamethylcyclotetrasiloxane 556-67-2	LogPow	6.98
	Temperature	21.7 °C
	Method	other guideline:

Section 13. Disposal considerations

Product

Method of disposal:
Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages:
Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:
Not dangerous goods

Railroad transport RID:
Not dangerous goods

Inland water transport ADN:
Not dangerous goods

Marine transport IMDG:
Not dangerous goods

Air transport IATA:
Not dangerous goods

Section 15. Regulatory information

Regulatory Information:
Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
ENCS (JP)	yes
IECSC	yes
AIIC	yes
TCSI	yes
PICCS (PH)	yes
EINECS	yes

Section 16. Other information

Disclaimer:
This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.
This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).