Safety Data Sheet

LOCTITE 572 PIPE SEALANT 50 ML EN/JP/KR

SDS No. : 153495
V002.12
Revision: 15.01.2025
printing date: 04.11.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:
LOCTITE 572 PIPE SEALANT 50 ML EN/JP/KR

Other means of identification:
LOCTITE 572 PIPE SEALANT 50 ML EN/JP/KR

Product code:
IDH378301

Recommended use of the chemical and restrictions on use

Intended use:
Adhesive

Manufacturer/Importer/Distributor Representative Company

Henkel Thailand Ltd. The Offices at Centralworld,
35th Floor, 999/9 Rama 1 Rd.,
Kwang Patumwan, Khet Patumwan,
10330 Bangkok

Thailand

Phone: +66 (2209) 8000
Fax-no.: +66 (2209) 8008

E-mail address of person responsible for Safety Data Sheet:
ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents:
FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +662 209 8008

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category
Serious eye damage/eye irritation	Category 2

GHS label elements:

Hazard pictogram:



Signal word:
Warning

Hazard statement:
H319 Causes serious eye irritation.

Precaution:

Prevention:
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Mica 12001-26-2	10- 30 %	
Octan-1-ol 111-87-5	10- 30 %	Flammable liquids 4 H227 Acute toxicity 5; Dermal H313 Skin corrosion/irritation 3 H316 Serious eye damage/eye irritation 2A H319 Acute hazards to the aquatic environment 3 H402 Chronic hazards to the aquatic environment 3 H412
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	1- 10 %	
Silica, amorphous, fumed, cryst.-free 112945-52-5	1- 10 %	
α, α-dimethylbenzyl hydroperoxide 80-15-9	0.1- 1 %	Flammable liquids 4 H227 Organic peroxides E H242 Acute toxicity 4; Oral H302 Acute toxicity 2; Inhalation H330 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 1 H314 Specific target organ toxicity - single exposure 3 H335 Specific target organ toxicity - repeated exposure 2 H373 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	0.1- 1 %	Flammable liquids 4 H227 Acute toxicity 5; Oral H303 Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Skin sensitizer 1B H317 Acute hazards to the aquatic environment 3 H402

Section 4. First aid measures

Inhalation:
Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:
Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:
Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Indication of immediate medical attention and special treatment needed:
See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:
Carbon dioxide, foam, powder

Specific hazards arising from the chemical:
In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

Special protection equipment and precautions for firefighters:
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products:
Oxides of carbon, oxides of nitrogen, irritating organic vapors.

Additional fire fighting advice:
In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:
Avoid skin and eye contact.
Ensure adequate ventilation.
Wear protective equipment.
See advice in section 8

Environmental precautions:
Do not empty into drains / surface water / ground water.

Clean-up methods:
For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:
Use only in well-ventilated areas.
Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.
Avoid skin and eye contact.
See advice in section 8

Storage:
Refer to Technical Data Sheet.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

MICA, RESPIRABLE DUST 12001-26-2	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	TH OEL
Mica, respirable fraction 12001-26-2	**Value type**	Time Weighted Average (TWA):
	mg/m³	0.1
	Remarks	ACGIH
Titanium dioxide, nanoscale particles, respirable fraction 13463-67-7	**Value type**	Time Weighted Average (TWA):
	mg/m³	0.2
	Remarks	ACGIH
Titanium dioxide, finescale particles, respirable fraction 13463-67-7	**Value type**	Time Weighted Average (TWA):
	mg/m³	2.5
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles 112945-52-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles 112945-52-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Wear protective glasses.
Protective eye equipment should conform to EN166.

Body protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:
Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures:
The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Off white paste
Odor:	alcohol-like
Odor threshold (CA):	No data available.
pH:	3 - 6
Melting point / freezing point:	No data available.
Specific gravity:	1.08
Boiling point:	No data available.
Flash point:	> 100 °C (> 212 °F)
Evaporation rate:	Not available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure: (; 68 °F (20 °C))	< 0.5 mm hg
Vapor density:	No data available.
Density:	1.25 g/cm3
Solubility:	Not miscible
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content: (2010/75/EC)	< 3 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials:
Reaction with strong acids.
Reacts with strong oxidants.
Chemical stability:
Stable under recommended storage conditions.
Conditions to avoid:
None if used for intended purpose.
Hazardous decomposition products:
Irritating organic vapours.

Section 11. Toxicological information

Inhalative toxicity: Acute toxicity estimate (ATE) : > 20 mg/l
Exposure time: 4 h
Test atmosphere: Vapor.
Method: Calculation method

Health Effects:
Eyes: Causes serious eye irritation.
Symptoms of Overexposure**:** EYE: Irritation, conjunctivitis.
Prolonged or repeated contact may cause skin irritation.

Acute oral toxicity:

Mica 12001-26-2	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	not specified
Octan-1-ol 111-87-5	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
Silica, amorphous, fumed, cryst.-free 112945-52-5	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	LD50
	Value	382 mg/kg
	Species	rat
	Method	other guideline:
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Value type	LD50
	Value	2,790 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Value type	LC50
	Value	> 6.82 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified
Silica, amorphous, fumed, cryst.-free 112945-52-5	Value type	LC0
	Value	0.139 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	LC50
	Value	1.370 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified

Acute dermal toxicity:

Octan-1-ol 111-87-5	Value type	LD50
	Value	2,000 - 4,000 mg/kg
	Species	rabbit
	Method	
Octan-1-ol 111-87-5	Value type	Acute toxicity estimate (ATE)
	Value	2,500 mg/kg
	Species	
	Method	Expert judgement
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Value type	LD50
	Value	>= 10,000 mg/kg
	Species	hamster
	Method	not specified
Silica, amorphous, fumed, cryst.-free 112945-52-5	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	Acute toxicity estimate (ATE)
	Value	1,100 mg/kg
	Species	
	Method	Expert judgement
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Value type	LD50
	Value	5,610 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Octan-1-ol 111-87-5	Result	slightly irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Silica, amorphous, fumed, cryst.-free 112945-52-5	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Result	corrosive
	Exposure time	
	Species	rabbit
	Method	Draize Test
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Result	irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Octan-1-ol 111-87-5	Result	irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Silica, amorphous, fumed, cryst.-free 112945-52-5	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Result	irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Octan-1-ol 111-87-5	Result	not sensitising
	Test type	Draize Test
	Species	guinea pig
	Method	Draize Test
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

Octan-1-ol 111-87-5	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Octan-1-ol 111-87-5	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Octan-1-ol 111-87-5	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Silica, amorphous, fumed, cryst.-free 112945-52-5	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	
	Method	not specified
Silica, amorphous, fumed, cryst.-free 112945-52-5	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	
	Method	not specified
Silica, amorphous, fumed, cryst.-free 112945-52-5	Result	negative
	Type of study / Route of administration	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro
	Metabolic activation / Exposure time	
	Method	not specified
α, α-dimethylbenzyl hydroperoxide 80-15-9	Result	positive
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Result	negative
	Type of study / Route of administration	dermal
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Dimethyl-2,7-Octadien-6-ol, 2,6-	Result	negative

78-70-6	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity:

Octan-1-ol 111-87-5	Result	NOAEL=1,000 mg/kg
	Route of application	dermal
	Exposure time / Frequency of treatment	90 d6 h/d, 5 d/w
	Species	rat
	Method	OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Result	NOAEL=1,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	90 ddaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Result	
	Route of application	inhalation: aerosol
	Exposure time / Frequency of treatment	6 h/d5 d/w
	Species	rat
	Method	not specified
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Result	NOAEL=117 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	28 ddaily
	Species	rat
	Method	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity:

Toxicity:

Mica 12001-26-2	Value type	LC50
	Value	400 mg/l
	Acute Toxicity Study	Fish
	Exposure time	48 h
	Species	Leuciscus idus
	Method	DIN 38412-15
Mica 12001-26-2	Value type	EC50
	Value	2,808 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Mica 12001-26-2	Value type	EC0
	Value	1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	Pseudomonas putida
	Method	DIN 38412, part 27 (Bacterial oxygen consumption test)
Octan-1-ol 111-87-5	Value type	LC50
	Value	13.3 mg/l

	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Octan-1-ol 111-87-5	Value type	EC50
	Value	47 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Octan-1-ol 111-87-5	Value type	EC10
	Value	4.2 mg/l
	Acute Toxicity Study	Algae
	Exposure time	48 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	DIN 38412-09
	Value type	EC50
	Value	14 mg/l
	Acute Toxicity Study	Algae
	Exposure time	48 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	DIN 38412-09
Octan-1-ol 111-87-5	Value type	EC 50
	Value	350 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	48 h
	Species	Danio rerio
	Method	other guideline:
	Value type	NOEC
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	8 d
	Species	Danio rerio
	Method	OECD Guideline 212 (Fish, Short-term Toxicity Test on Embryo and Sac-Fry Stages)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge
	Method	ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)
Silica, amorphous, fumed, cryst.-free 112945-52-5	Value type	LC50
	Value	> 10,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)

	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	LC50
	Value	3.9 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	EC50
	Value	18.84 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	EC50
	Value	3.1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	EC10
	Value	70 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	not specified
	Method	not specified
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Value type	LC50
	Value	27.8 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Salmo gairdneri (new name: Oncorhynchus mykiss)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Value type	EC50
	Value	59 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Value type	EC50
	Value	88.3 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC10
	Value	38.4 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Value type	EC0
	Value	100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

Octan-1-ol 111-87-5	Result	readily biodegradable
	Route of application	aerobic
	Degradability	92 %
	Method	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)

α, α-dimethylbenzyl hydroperoxide 80-15-9	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	3 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Result	readily biodegradable
	Route of application	aerobic
	Degradability	> 97.1 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
	Result	inherently biodegradable
	Route of application	
	Degradability	100 %
	Method	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)

Bioaccumulative potential / Mobility in soil:

Octan-1-ol 111-87-5	LogPow	3.5
	Temperature	23 °C
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Bioconcentration factor (BCF)	9.1
	Exposure time	
	Species	calculation
	Temperature	
	Method	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	LogPow	1.6
	Temperature	25 °C
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	LogPow	3.1
	Temperature	25 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

Section 13. Disposal considerations

Product

Method of disposal:
Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages:
Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:
Not dangerous goods

Railroad transport RID:
Not dangerous goods

Inland water transport ADN:
Not dangerous goods

Marine transport IMDG:
Not dangerous goods

Air transport IATA:
Not dangerous goods

Section 15. Regulatory information

Regulatory Information:
Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
ENCS (JP)	yes
ISHL (JP)	yes
IECSC	yes
AIIC	yes
TCSI	yes
EINECS	yes

Section 16. Other information

Disclaimer:
This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.
This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).