Safety Data Sheet

LOCTITE 2422 HI TEMP TL 300G

SDS No. : 292259
V001.7
Revision: 13.01.2025
printing date: 04.11.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:
LOCTITE 2422 HI TEMP TL 300G

Other means of identification:
LOCTITE 2422 HI TEMP TL 300G

Product code:
IDH2946244

Recommended use of the chemical and restrictions on use

Intended use:
Anaerobic Adhesive

Manufacturer/Importer/Distributor Representative Company

Henkel Thailand Ltd. The Offices at Centralworld,
35th Floor, 999/9 Rama 1 Rd.,
Kwang Patumwan, Khet Patumwan,
10330 Bangkok

Thailand

Phone: +66 (2209) 8000
Fax-no.: +66 (2209) 8008

E-mail address of person responsible for Safety Data Sheet:
ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents:
FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +662 209 8008

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category
Skin sensitizer	Category 1
Toxic to reproduction	Category 1B
Acute hazards to the aquatic environment	Category 1
Chronic hazards to the aquatic environment	Category 1

GHS label elements:

Hazard pictogram:



Signal word:
Danger

Hazard statement:
H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.
H410 Very toxic to aquatic life with long lasting effects.

Precaution:

Prevention:
P201 Obtain special instructions before use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:
P302+P352 IF ON SKIN: Wash with plenty of water.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.

Disposal:
P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Boric acid 10043-35-3	30- 60 %	Acute toxicity 5; Oral H303 Toxic to reproduction 1B H360
Polyamide wax Proprietary	1- 10 %	Skin sensitizer 1 H317 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410
Ethene, homopolymer 9002-88-4	1- 10 %	
Silica, amorphous, fumed, crystal-free 112945-52-5	1- 10 %	
α, α-dimethylbenzyl hydroperoxide 80-15-9	0.1- 1 %	Flammable liquids 4 H227 Organic peroxides E H242 Acute toxicity 4; Oral H302 Acute toxicity 2; Inhalation H330 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 1 H314 Specific target organ toxicity - single exposure 3 H335 Specific target organ toxicity - repeated exposure 2 H373 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
N,N-Diethyl-p-toluidine 613-48-9	0.1- 1 %	Flammable liquids 4 H227 Acute toxicity 3; Oral H301 Acute toxicity 3; Inhalation H331 Acute toxicity 3; Dermal H311 Skin corrosion/irritation 2 H315 Specific target organ toxicity - repeated exposure 2 H373 Acute hazards to the aquatic environment 3 H402 Chronic hazards to the aquatic environment 3 H412
mequinol 150-76-5	0.1- 1 %	Flammable liquids 4 H227 Acute toxicity 4; Oral H302 Acute toxicity 5; Dermal H313 Skin corrosion/irritation 3 H316 Serious eye damage/eye irritation 2A H319 Skin sensitizer 1 H317 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 3 H412

Section 4. First aid measures

Inhalation:
Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:
Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Indication of immediate medical attention and special treatment needed:
See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:
Carbon dioxide, foam, powder
Fine water spray

Improper extinguishing media:
None known

Specific hazards arising from the chemical:
In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

Special protection equipment and precautions for firefighters:
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional fire fighting advice:
In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:
Avoid skin and eye contact.
Ensure adequate ventilation.

Environmental precautions:
Do not let product enter drains.

Clean-up methods:
For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Section 7. Handling and storage

Handling:
Use only in well-ventilated areas.
Avoid skin and eye contact.
Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Storage:
Ensure good ventilation/extraction.
Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

PARTICLES (INSOLUBLE OR POORLY SOLUBLE) NOT OTHERWISE SPECIFIED, INHALABLE PARTICLES 9002-88-4	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
PARTICLES (INSOLUBLE OR POORLY SOLUBLE) NOT OTHERWISE SPECIFIED, RESPIRABLE PARTICLES 9002-88-4	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
Silica, amorphous, fumed, crystal-free 112945-52-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
Silica, amorphous, fumed, crystal-free 112945-52-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles 112945-52-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles 112945-52-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
4-METHOXYPHENOL 150-76-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	5
	Remarks	ACGIH

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Wear protective glasses.
Protective eye equipment should conform to EN166.

Body protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:
Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures:
The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Blue paste
Odor:	characteristic
Odor threshold (CA):	No data available.
pH:	Not applicable, Product is non-polar/aprotic.
Melting point / freezing point:	No data available.
Specific gravity:	1.1762
Boiling point:	> 150 °C (> 302 °F)
Flash point:	> 100 °C (> 212 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure: (; 20 °C (68 °F))	< 0.13 mbar
Vapor density:	> 1
Density:	No data available.
Solubility:	No data available.
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content: (2010/75/EC)	< 3 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials:
Peroxides.
Chemical stability:
Stable under recommended storage conditions.
Conditions to avoid:
No decomposition if used according to specifications.
Hazardous decomposition products:
Oxides of carbon.

Section 11. Toxicological information

Oral toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg
Method: Calculation method

Inhalative toxicity: Acute toxicity estimate (ATE) : > 20 mg/l
Exposure time: 4 h
Test atmosphere: Vapor.
Method: Calculation method

Dermal toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg
Method: Calculation method

Symptoms of Overexposure**:** May impair fertility.
May cause harm to the unborn child.

Acute oral toxicity:

Boric acid 10043-35-3	Value type	LD50
	Value	3,450 mg/kg
	Species	rat
	Method	not specified
Polyamide wax Proprietary	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	other guideline:
Ethene, homopolymer 9002-88-4	Value type	Acute toxicity estimate (ATE)
	Value	> 5,000 mg/kg
	Species	
	Method	Expert judgement
Silica, amorphous, fumed, crystal-free 112945-52-5	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	LD50
	Value	382 mg/kg
	Species	rat
	Method	other guideline:
N,N-Diethyl-p-toluidine 613-48-9	Value type	Acute toxicity estimate (ATE)
	Value	100 mg/kg
	Species	
	Method	Expert judgement
mequinol 150-76-5	Value type	LD50
	Value	1,630 mg/kg
	Species	rat
	Method	not specified

Acute inhalative toxicity:

Ethene, homopolymer 9002-88-4	Value type	Acute toxicity estimate (ATE)
	Value	> 5 mg/l
	Exposure time	4 h
	Species	
	Method	Expert judgement
Silica, amorphous, fumed, crystal-free 112945-52-5	Value type	LC50
	Value	> 58.8 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	LC50
	Value	1.370 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified
N,N-Diethyl-p-toluidine 613-48-9	Value type	Acute toxicity estimate (ATE)
	Value	3 mg/l
	Exposure time	
	Species	
	Method	Expert judgement

Acute dermal toxicity:

Boric acid 10043-35-3	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rabbit
	Method	not specified
Polyamide wax Proprietary	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	other guideline:
Ethene, homopolymer 9002-88-4	Value type	Acute toxicity estimate (ATE)
	Value	> 5,000 mg/kg
	Species	
	Method	Expert judgement
Silica, amorphous, fumed, crystal-free 112945-52-5	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	Acute toxicity estimate (ATE)
	Value	1,100 mg/kg
	Species	
	Method	Expert judgement
N,N-Diethyl-p-toluidine 613-48-9	Value type	Acute toxicity estimate (ATE)
	Value	300 mg/kg
	Species	
	Method	Expert judgement
mequinol 150-76-5	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	EU Method B.3 (Acute Toxicity (Dermal)
mequinol 150-76-5	Value type	Acute toxicity estimate (ATE)
	Value	2,500 mg/kg
	Species	
	Method	Expert judgement

Skin corrosion/irritation:

Boric acid 10043-35-3	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	not specified
Silica, amorphous, fumed, crystal-free 112945-52-5	Result	not irritating
	Exposure time	
	Species	rabbit

	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Result	corrosive
	Exposure time	
	Species	rabbit
	Method	Draize Test
N,N-Diethyl-p-toluidine 613-48-9	Result	irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
mequinol 150-76-5	Result	mildly irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Boric acid 10043-35-3	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Ethene, homopolymer 9002-88-4	Result	not irritating
	Exposure time	24 h
	Species	rabbit
	Method	FDA Guideline
Silica, amorphous, fumed, crystal-free 112945-52-5	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Boric acid 10043-35-3	Result	not sensitising
	Test type	Buehler test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
Polyamide wax Proprietary	Result	sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
Polyamide wax Proprietary	Result	sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
Ethene, homopolymer 9002-88-4	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
mequinol 150-76-5	Result	sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Boric acid 10043-35-3	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Boric acid 10043-35-3	Result	negative
	Type of study / Route of administration	sister chromatid exchange assay in mammalian cells
	Metabolic activation / Exposure time	with and without
	Method	not specified
Boric acid 10043-35-3	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Boric acid 10043-35-3	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Ethene, homopolymer 9002-88-4	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	Ames Test
Silica, amorphous, fumed, crystal-free 112945-52-5	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Silica, amorphous, fumed, crystal-free 112945-52-5	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Silica, amorphous, fumed, crystal-free 112945-52-5	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Result	positive
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Result	negative
	Type of study / Route of administration	dermal
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified

Repeated dose toxicity:

Boric acid 10043-35-3	Result	NOAEL=100 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	2 ydaily
	Species	rat
	Method	not specified
Silica, amorphous, fumed, crystal-free 112945-52-5	Result	NOAEL=< 0.046 mg/l
	Route of application	inhalation
	Exposure time / Frequency of treatment	14 days6 hours/day, 5 days/week
	Species	rat
	Method	not specified
Silica, amorphous, fumed, crystal-free 112945-52-5	Result	NOAEL=> 4,500 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	13 weeksdaily, continous
	Species	rat
	Method	
α, α-dimethylbenzyl hydroperoxide 80-15-9	Result	
	Route of application	inhalation: aerosol
	Exposure time / Frequency of treatment	6 h/d5 d/w
	Species	rat
	Method	not specified

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H410 Very toxic to aquatic life with long lasting effects.

Toxicity:

Boric acid 10043-35-3	Value type	LC50
	Value	455 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	other guideline:
	Value type	NOEC
	Value	36.6 mg/l
	Acute Toxicity Study	Fish
	Exposure time	34 d
	Species	Danio rerio (reported as Brachydanio rerio)
	Method	OECD Guideline 210 (fish early lite stage toxicity test)
Boric acid 10043-35-3	Value type	EC50
	Value	520 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Ceriodaphnia dubia
	Method	other guideline:
Boric acid 10043-35-3	Value type	EC50
	Value	299.6 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC10
	Value	200.12 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Boric acid 10043-35-3	Value type	EC0
	Value	20 mg/l

	Acute Toxicity Study	Bacteria
	Exposure time	16 h
	Species	Pseudomonas putida
	Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
Polyamide wax Proprietary	Value type	LC50
	Value	> 0.2 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	carp
	Method	not specified
Polyamide wax Proprietary	Value type	EL50
	Value	15.63 - 250 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Polyamide wax Proprietary	Value type	ErC50
	Value	0.0012 mg/l
	Acute Toxicity Study	Algae
	Exposure time	48 h
	Species	Skeletonema costatum
	Method	ISO 10253 (Water quality)
	Value type	EC10
	Value	0.00087 mg/l
	Acute Toxicity Study	Algae
	Exposure time	48 h
	Species	Skeletonema costatum
	Method	ISO 10253 (Water quality)
Ethene, homopolymer 9002-88-4	Value type	LC50
	Value	> 100 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethene, homopolymer 9002-88-4	Value type	EC0
	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	not specified
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Silica, amorphous, fumed, crystal-free 112945-52-5	Value type	LC50
	Value	> 10,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Silica, amorphous, fumed, crystal-free 112945-52-5	Value type	EL50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Silica, amorphous, fumed, crystal-free 112945-52-5	Value type	NOELR
	Value	10,000 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EL50
	Value	> 10,000 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Silica, amorphous, fumed, crystal-free 112945-52-5	Value type	EC0
	Value	10,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	Pseudomonas putida
	Method	DIN 38412, part 27 (Bacterial oxygen consumption test)

α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	LC50
	Value	3.9 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	EC50
	Value	18.84 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	EC50
	Value	3.1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Value type	EC10
	Value	70 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	not specified
	Method	not specified
N,N-Diethyl-p-toluidine 613-48-9	Value type	LC50
	Value	78.62 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Danio rerio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
N,N-Diethyl-p-toluidine 613-48-9	Value type	EC50
	Value	10.34 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
N,N-Diethyl-p-toluidine 613-48-9	Value type	EC50
	Value	23.69 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
mequinol 150-76-5	Value type	LC50
	Value	28.5 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
mequinol 150-76-5	Value type	EC50
	Value	3 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
mequinol 150-76-5	Value type	EC50
	Value	54.7 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	2.96 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata

	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)

Persistence and degradability:

Polyamide wax Proprietary	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	69.3 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Ethene, homopolymer 9002-88-4	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	1 %
	Method	ISO 10708 (BODIS-Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	3 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
N,N-Diethyl-p-toluidine 613-48-9	Result	not readily biodegradable.
	Route of application	not specified
	Degradability	1 %
	Method	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
mequinol 150-76-5	Result	readily biodegradable
	Route of application	aerobic
	Degradability	86 %
	Method	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

Bioaccumulative potential / Mobility in soil:

Boric acid 10043-35-3	Bioconcentration factor (BCF)	< 0.1
	Exposure time	90 d
	Species	Oncorhynchus tschawytscha
	Temperature	12 °C
	Method	not specified
Boric acid 10043-35-3	LogPow	-1.09
	Temperature	22 °C
	Method	EU Method A.8 (Partition Coefficient)
Polyamide wax Proprietary	LogPow	5.4 - 6.6
	Temperature	25 °C
	Method	EU Method A.8 (Partition Coefficient)
Silica, amorphous, fumed, crystal-free 112945-52-5	LogPow	0.53
	Temperature	
	Method	QSAR (Quantitative Structure Activity Relationship)
α, α-dimethylbenzyl hydroperoxide 80-15-9	Bioconcentration factor (BCF)	9.1
	Exposure time	
	Species	calculation
	Temperature	
	Method	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	LogPow	1.6
	Temperature	25 °C
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
N,N-Diethyl-p-toluidine 613-48-9	LogPow	3.7
	Temperature	
	Method	QSAR (Quantitative Structure Activity Relationship)
mequinol 150-76-5	LogPow	1.58
	Temperature	
	Method	EU Method A.8 (Partition Coefficient)

Section 13. Disposal considerations

Product

Method of disposal:
Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages:
Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Class:	9
Packing group:	III
Classification code:	M6
Hazard ident. number:	90
UN no.:	3082
Label:	9
Technical name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diamid wax mixture)

Railroad transport RID:

Class:	9
Packing group:	III
Classification code:	M6
Hazard ident. number:	90
UN no.:	3082
Label:	9
Technical name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diamid wax mixture)

Inland water transport ADN:

Class:	9
Packing group:	III
Classification code:	M6
Hazard ident. number:	90
UN no.:	3082
Label:	9
Technical name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diamid wax mixture)

Marine transport IMDG:

Class:	9
Packing group:	III
UN no.:	3082
Label:	9
EmS:	F-A ,S-F
Seawater pollutant:	Marine pollutant
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diamid wax mixture)

Air transport IATA:

Class:	9
Packing group:	III
Packaging instructions (passenger):	964
Packaging instructions (cargo):	964
UN no.:	3082
Label:	9
Proper shipping name:	Environmentally hazardous substance, liquid, n.o.s. (Diamid wax mixture)

Further information for transport:

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG), NZ 4.3(10) may be applied, which can result in a deviation from the transport classification for packed goods.

Section 15. Regulatory information

Regulatory Information:
Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
AIIC	yes
NZIOC	yes
TCSI	yes
IECSC	yes

Section 16. Other information

Disclaimer:
This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.
This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).