Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:
LOCTITE EA 0151 A 2.6LB

Other means of identification:
LOCTITE EA 0151 A 2.6LB

Product code:
IDH893470

Recommended use of the chemical and restrictions on use

Intended use:
Part A of 2-K-Epoxy Adhesive

Manufacturer/Importer/Distributor Representative Company

Henkel Thailand Ltd. The Offices at Centralworld,
35th Floor, 999/9 Rama 1 Rd.,
Kwang Patumwan, Khet Patumwan,
10330 Bangkok

Thailand

Phone: +66 (2209) 8000
Fax-no.: +66 (2209) 8008

E-mail address of person responsible for Safety Data Sheet:
ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents:
FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +662 209 8008

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitizer	Category 1
Germ cell mutagenicity	Category 2
Carcinogenicity	Category 2
Toxic to reproduction	Category 2
Chronic hazards to the aquatic environment	Category 2

GHS label elements:

Hazard pictogram:



Signal word:
Warning

Hazard statement:
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H411 Toxic to aquatic life with long lasting effects.

Precaution:

Prevention:
P201 Obtain special instructions before use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.

Disposal:
P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	60- 100 %	Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Skin sensitizer 1 H317 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
butyl glycidyl ether 2426-08-6	10- 30 %	Flammable liquids 3 H226 Acute toxicity 4; Oral H302 Acute toxicity 4; Inhalation H332 Acute toxicity 5; Dermal H313 Skin sensitizer 1 H317 Germ cell mutagenicity 2 H341 Carcinogenicity 2 H351 Toxic to reproduction 2 H361 Specific target organ toxicity - single exposure 3 H335 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
Silica, amorphous, fumed, cryst.-free 112945-52-5	1- 10 %	
4,4'-Isopropylidenediphenol 80-05-7	< 0.1 %	Acute toxicity 5; Oral H303 Acute toxicity 5; Dermal H313 Serious eye damage/eye irritation 1 H318 Skin sensitizer 1 H317 Toxic to reproduction 1B H360 Specific target organ toxicity - single exposure 3 H335 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410

Section 4. First aid measures

Inhalation:
Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:
Immediately wash skin thoroughly with soap and water.
Obtain medical attention if irritation persists.

Eye contact:
Wash with plenty of water immediately and continue for several minutes, holding eyelid open. Consult a doctor.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Section 5. Fire fighting measures

Suitable extinguishing media:
Foam, extinguishing powder, carbon dioxide.
Water spray jet

Improper extinguishing media:
High pressure waterjet

Specific hazards arising from the chemical:
Danger of decomposition if exposed to heat.
In case of fire, keep containers cool with water spray.
Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.

Special protection equipment and precautions for firefighters:
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products:
See section 10.

Section 6. Accidental release measures

Personal precautions:
Ensure adequate ventilation.
Avoid contact with skin and eyes.
Wear protective equipment.
See advice in section 8

Environmental precautions:
Do not empty into drains / surface water / ground water.

Clean-up methods:
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:
Ensure good ventilation/suction at the workplace.
Extract when the product is heated.
See advice in section 8
Avoid skin and eye contact.

Storage:
Store in sealed original container.
Protect against contamination.
Store in a cool, dry place.
Ensure that storage and workrooms are adequately ventilated.
Must be stored in a room with spill collection facilities.
Keep away from heat and direct sunlight.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

N-BUTYL GLYCIDYL ETHER (BGE) 2426-08-6	**Value type**	Time Weighted Average (TWA):
	ppm	3
	Remarks	ACGIH
N-BUTYL GLYCIDYL ETHER (BGE) 2426-08-6	**Value type**	Time Weighted Average (TWA):
	ppm	50
	Remarks	TH OEL
N-BUTYL GLYCIDYL ETHER (BGE) 2426-08-6	**Value type**	Skin designation:
	Remarks	ACGIH Danger of cutaneous absorption
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles 112945-52-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles 112945-52-5	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; >= 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; >= 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Body protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:
Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures:
The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	White paste
Odor:	Mild
Odor threshold (CA):	No data available.
pH:(Concentration: 100 % product)	7 Approximately
Melting point / freezing point:	Not applicable, Product is a liquid
Specific gravity:	1.13
Boiling point:	140 °C (284 °F)
Flash point: (Pensky Martens closed cup)	81 °C (177.8 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure:	No data available.
Vapor density:	> 1
Density:	1.13 g/cm3
Solubility:	Not miscible or difficult to mix (20 °C)
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	Not available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content:	No data available.

Section 10. Stability and reactivity

Reactivity/Incompatible materials:
Reacts with alcohols and amines.
Reacts with oxidants, acids and lyes
Reaction with some curing agents may produce an exothermic reaction which in large masses could cause runaway polymerization.
Chemical stability:
Stable under recommended storage conditions.
Possibility of hazardous reactions:
Rapid polymerization may generate excessive heat and pressure.
Conditions to avoid:
Stable under normal conditions of storage and use.
Excessive heat.
Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately.
Failure to observe these precautions may result in excessive heat build-up causing an exotherm.
Danger of decomposition if exposed to heat.
Hazardous decomposition products:
Hydrocarbons
carbon oxides.
Polymerization may occur at elevated temperature or in the presence of incompatible materials.
May produce fumes when heated to decomposition. Fumes may contain carbon monoxide and other toxic fumes.
See section 5.

Section 11. Toxicological information

Oral toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method
Inhalative toxicity:	Acute toxicity estimate (ATE) : > 20 mg/l Exposure time: 4 h Test atmosphere: Vapor

Method: Calculation method

Health Effects:

Skin: Causes skin irritation.
May cause an allergic skin reaction.
Eyes: Causes serious eye irritation.
Symptoms of Overexposure**:** None known.

Acute oral toxicity:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 420 (Acute Oral Toxicity)
butyl glycidyl ether 2426-08-6	Value type	LD50
	Value	1,530 mg/kg
	Species	mouse
	Method	not specified
Silica, amorphous, fumed, cryst.-free 112945-52-5	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
4,4'-Isopropylidenediphenol 80-05-7	Value type	LD50
	Value	> 2,000 - < 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
4,4'-Isopropylidenediphenol 80-05-7	Value type	Acute toxicity estimate (ATE)
	Value	2,500 mg/kg
	Species	
	Method	Expert judgement

Acute inhalative toxicity:

butyl glycidyl ether 2426-08-6	Value type	LC50
	Value	10.97 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified
Silica, amorphous, fumed, cryst.-free 112945-52-5	Value type	LC50
	Value	> 5.01 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class (ATC) Method)

Acute dermal toxicity:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
butyl glycidyl ether 2426-08-6	Value type	LD50
	Value	2,520 mg/kg
	Species	rabbit
	Method	not specified
Silica, amorphous, fumed, cryst.-free 112945-52-5	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
4,4'-Isopropylidenediphenol 80-05-7	Value type	LD50
	Value	3,000 mg/kg
	Species	rabbit
	Method	not specified

Skin corrosion/irritation:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	irritating
	Exposure time	
	Species	
	Method	Weight of evidence
Silica, amorphous, fumed, cryst.-free 112945-52-5	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	irritating
	Exposure time	
	Species	
	Method	Weight of evidence
Silica, amorphous, fumed, cryst.-free 112945-52-5	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Silica, amorphous, fumed, cryst.-free 112945-52-5	Result	not sensitising
	Test type	
	Species	human
	Method	not specified
4,4'-Isopropylidenediphenol 80-05-7	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified
Silica, amorphous, fumed, cryst.-free 112945-52-5	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	
	Method	not specified
Silica, amorphous, fumed, cryst.-free 112945-52-5	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	
	Method	not specified
Silica, amorphous, fumed, cryst.-free 112945-52-5	Result	negative
	Type of study / Route of administration	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro
	Metabolic activation / Exposure time	
	Method	not specified
4,4'-Isopropylidenediphenol 80-05-7	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	not specified

Repeated dose toxicity:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	NOAEL=50 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	14 wdaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H411 Toxic to aquatic life with long lasting effects.

Toxicity:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	LC50
	Value	1.75 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	EC50
	Value	1.7 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	EC50
	Value	> 11 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	4.2 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	IC50
	Value	> 100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge, industrial
	Method	other guideline:
butyl glycidyl ether 2426-08-6	Value type	LC50
	Value	65 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Salmo gairdneri (new name: Oncorhynchus mykiss)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
butyl glycidyl ether 2426-08-6	Value type	LC50
	Value	9.2 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	not specified
butyl glycidyl ether 2426-08-6	Value type	EC50
	Value	35 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Silica, amorphous, fumed, cryst.-free 112945-52-5	Value type	LC50
	Value	> 10,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Silica, amorphous, fumed, cryst.-free 112945-52-5	Value type	EL50
	Value	> 10,000 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Silica, amorphous, fumed, cryst.-free	Value type	EC50
	Value	> 173 mg/l

112945-52-5	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Silica, amorphous, fumed, cryst.-free 112945-52-5	Value type	EC50
	Value	> 2,500 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	Value type	LC50
	Value	4.6 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
	Value type	LOEC
	Value	0.000372 mg/l
	Acute Toxicity Study	Fish
	Exposure time	300 d
	Species	Danio rerio
	Method	OECD Guideline 234 (Fish Sexual Development Test)
4,4'-Isopropylidenediphenol 80-05-7	Value type	EC50
	Value	0.885 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Acartia clausi
	Method	other guideline:
4,4'-Isopropylidenediphenol 80-05-7	Value type	EC50
	Value	3.73 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	other:
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC10
	Value	2.1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	Value type	EC10
	Value	> 320 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	18 h
	Species	Pseudomonas putida
	Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)

Persistence and degradability:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	5 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
butyl glycidyl ether 2426-08-6	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	25 %
	Method	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
4,4'-Isopropylidenediphenol 80-05-7	Result	readily biodegradable
	Route of application	aerobic
	Degradability	89 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

Bioaccumulative potential / Mobility in soil:

4,4'-Isopropylidenediphenol, oligomeric reaction products	LogPow	3.242
	Temperature	25 °C

with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Method	EU Method A.8 (Partition Coefficient)
butyl glycidyl ether 2426-08-6	LogPow	0.63
	Temperature	
	Method	QSAR (Quantitative Structure Activity Relationship)
4,4'-Isopropylidenediphenol 80-05-7	Bioconcentration factor (BCF)	5.1 - 67
	Exposure time	42 d
	Species	Cyprinus carpio
	Temperature	25 °C
	Method	other guideline:
4,4'-Isopropylidenediphenol 80-05-7	LogPow	3.4
	Temperature	21.5 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

Section 13. Disposal considerations

Product

Method of disposal:
Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages:
Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Class:	9
Packing group:	III
Classification code:	M6
Hazard ident. number:	90
UN no.:	3082
Label:	9
Technical name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)

Railroad transport RID:

Class:	9
Packing group:	III
Classification code:	M6
Hazard ident. number:	90
UN no.:	3082
Label:	9
Technical name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)

Inland water transport ADN:

Class:	9
Packing group:	III
Classification code:	M6
Hazard ident. number:	90
UN no.:	3082
Label:	9
Technical name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)

Marine transport IMDG:

Class:	9
Packing group:	III
UN no.:	3082
Label:	9
EmS:	F-A ,S-F
Seawater pollutant:	Marine pollutant
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)

Air transport IATA:

Class:	9
Packing group:	III
Packaging instructions (passenger):	964
Packaging instructions (cargo):	964
UN no.:	3082
Label:	9
Proper shipping name:	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin resin)

Further information for transport:

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG), NZ 4.3(10) may be applied, which can result in a deviation from the transport classification for packed goods.

Section 15. Regulatory information

Regulatory Information:
Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

Global inventory status:

Regulatory list	Notification
TCSI	yes
TSCA	yes
AIIC	yes
DSL	yes
ISHL (JP)	yes
KECI (KR)	yes
PICCS (PH)	yes
IECSC	yes

Section 16. Other information

Disclaimer:
This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.
This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).