Safety Data Sheet

LOCTITE EA E-00NS 55G PART B

SDS No. : 157197
V001.10
Revision: 24.01.2025
printing date: 04.11.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:
LOCTITE EA E-00NS 55G PART B

Other means of identification:
LOCTITE EA E-00NS 55G PART B

Product code:
IDH2946086

Recommended use of the chemical and restrictions on use

Intended use:
2-Component epoxy adhesive

Manufacturer/Importer/Distributor Representative Company

Henkel Thailand Ltd. The Offices at Centralworld,
35th Floor, 999/9 Rama 1 Rd.,
Kwang Patumwan, Khet Patumwan,
10330 Bangkok

Thailand

Phone: +66 (2209) 8000
Fax-no.: +66 (2209) 8008

E-mail address of person responsible for Safety Data Sheet:
ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents:
FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +662 209 8008

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category
Skin corrosion/irritation	Category 1B
Serious eye damage/eye irritation	Category 1
Skin sensitizer	Category 1
Chronic hazards to the aquatic environment	Category 3

GHS label elements:

Hazard pictogram:



Signal word:
Danger

Hazard statement:
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precaution:

Prevention:
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340+P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
Disposal:
P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	60- 100 %	Acute toxicity 5; Oral H303 Skin sensitizer 1B H317 Acute hazards to the aquatic environment 3 H402 Chronic hazards to the aquatic environment 3 H412
Benzyldimethylamine 103-83-3	1- 10 %	Flammable liquids 3 H226 Acute toxicity 4; Oral H302 Acute toxicity 3; Inhalation H331 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 1 H314 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
2-Aminoethanol 141-43-5	1- 10 %	Flammable liquids 4 H227 Acute toxicity 4; Oral H302 Acute toxicity 4; Inhalation H332 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 1 H314 Serious eye damage/eye irritation 1 H318 Specific target organ toxicity - single exposure 3 H335 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 3 H412

Section 4. First aid measures

Inhalation:
Move to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention.

Skin contact:
Immediately flush skin with plenty of water (using soap, if available).
Remove contaminated clothing and footwear.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
Get medical attention.

Eye contact:
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Get medical attention.

Ingestion:
DO NOT induce vomiting unless directed to do so by medical personnel.
Never give anything by mouth to an unconscious person.
Get medical attention.

Section 5. Fire fighting measures

Suitable extinguishing media:
Water spray (fog), foam, dry chemical or carbon dioxide.

Specific hazards arising from the chemical:
In case of fire, keep containers cool with water spray.
Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.

Special protection equipment and precautions for firefighters:
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products:
Oxides of carbon.
Oxides of nitrogen.
Oxides of sulfur.
Formaldehyde.
Hydrogen sulfide.
Toxic fumes.
Irritating vapors.

Section 6. Accidental release measures

Personal precautions:
Avoid skin and eye contact.
Wear protective equipment.
Ensure adequate ventilation.
See advice in section 8

Environmental precautions:
Do not empty into drains / surface water / ground water.

Clean-up methods:
Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Scrape up spilled material and place in a closed container for disposal.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:
Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.
Do not taste or swallow.
Use only with adequate ventilation.
Keep container closed.

Storage:
Store in original container until ready to use.
Store in a cool, well-ventilated place.
Keep away from sources of ignition.
Store at room temperature.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

ETHANOLAMINE 141-43-5	**Value type**	Short Term Exposure Limit (STEL):
	ppm	6
	Remarks	ACGIH
ETHANOLAMINE 141-43-5	**Value type**	Time Weighted Average (TWA):
	ppm	3
	Remarks	TH OEL
ETHANOLAMINE 141-43-5	**Value type**	Time Weighted Average (TWA):
	ppm	3
	Remarks	ACGIH

Respiratory protection:
Use a NIOSH approved air-purifying respirator with an organic vapor cartridge.

Hand protection:
Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; >= 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; >= 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety goggles or safety glasses with side shields.
Full face protection should be used if the potential for splashing or spraying of product exists.
Protective eye equipment should conform to EN166.

Body protection:
Protective clothing that covers arms and legs.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:
Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures:
The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Light, Cream Liquid
Odor:	Of sulphur dioxide
Odor threshold (CA):	No data available.
pH:	No data available.
Melting point / freezing point:	No data available.
Specific gravity:	1.12
Boiling point:	No data available.
Flash point:	258 °C (496.4 °F)
(Cleveland closed cup)	

Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Density:	No data available.
Solubility:	No data available.
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content:	< 1 % < 10 g/l

Section 10. Stability and reactivity

Reactivity/Incompatible materials:
Acids
Oxidizing agents.
Halogenated compounds.
Chemical stability:
Stable under recommended storage conditions.
Possibility of hazardous reactions:
None under normal processing.
Conditions to avoid:
Keep away from heat, ignition sources and incompatible materials.
Hazardous decomposition products:
Oxides of carbon.
Oxides of nitrogen.
Oxides of sulfur.
Formaldehyde
Hydrogen sulfide.
Toxic fumes.

Section 11. Toxicological information

Oral toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method
Inhalative toxicity:	Acute toxicity estimate (ATE) : > 20 mg/l Exposure time: 4 h Test atmosphere: Vapor. Method: Calculation method
Dermal toxicity:	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method

Symptoms of Overexposure**:** None known.

Acute oral toxicity:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Value type	LD50
	Value	2,600 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Benzyldimethylamine 103-83-3	Value type	LD50
	Value	353 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
2-Aminoethanol 141-43-5	Value type	LD50
	Value	1,089 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

Benzyldimethylamine 103-83-3	Value type	LC50
	Value	2.052 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified
2-Aminoethanol 141-43-5	Value type	Acute toxicity estimate (ATE)
	Value	1.5 mg/l
	Exposure time	
	Species	
	Method	Expert judgement
2-Aminoethanol 141-43-5	Value type	LC50
	Value	1 - 5 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified

Acute dermal toxicity:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Value type	LD50
	Value	> 10,200 mg/kg
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Benzyldimethylamine 103-83-3	Value type	LD50
	Value	1,477 mg/kg
	Species	rabbit
	Method	not specified
2-Aminoethanol 141-43-5	Value type	LD50
	Value	1,025 mg/kg
	Species	rabbit
	Method	not specified

Skin corrosion/irritation:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-Aminoethanol 141-43-5	Result	corrosive
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-Aminoethanol 141-43-5	Result	corrosive
	Exposure time	4 h
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-Aminoethanol 141-43-5	Result	corrosive
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2-Aminoethanol 141-43-5	Result	Category 1 (irreversible effects on the eye)
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Result	Sub-Category 1B (sensitising)
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2-Aminoethanol 141-43-5	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	not specified

Germ cell mutagenicity:

2-Aminoethanol 141-43-5	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-Aminoethanol 141-43-5	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	without
	Method	equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-Aminoethanol 141-43-5	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2-Aminoethanol 141-43-5	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity:

2-Aminoethanol 141-43-5	Result	NOAEL=300 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	> 75 ddaily
	Species	rat
	Method	other guideline:

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H412 Harmful to aquatic life with long lasting effects.

Toxicity:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptop 72244-98-5	Value type	LC50
	Value	87 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Danio rerio
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptop 72244-98-5	Value type	EC50
	Value	12 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptop 72244-98-5	Value type	EC50
	Value	> 733 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	338 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptop 72244-98-5	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Benzyldimethylamine 103-83-3	Value type	LC50
	Value	37.8 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Benzyldimethylamine 103-83-3	Value type	EC50
	Value	> 100 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	EU Method C.2 (Acute Toxicity for Daphnia)
Benzyldimethylamine 103-83-3	Value type	EC50
	Value	1.34 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	EU Method C.3 (Algal Inhibition test)
	Value type	NOEC
	Value	0.24 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)
	Method	EU Method C.3 (Algal Inhibition test)
Benzyldimethylamine 103-83-3	Value type	EC10
	Value	534 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	17 h
	Species	Pseudomonas putida
	Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
2-Aminoethanol 141-43-5	Value type	LC50
	Value	349 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Cyprinus carpio

	Method	EU Method C.1 (Acute Toxicity for Fish)
	Value type	NOEC
	Value	1.24 mg/l
	Acute Toxicity Study	Fish
	Exposure time	41 d
	Species	Oryzias latipes
	Method	OECD Guideline 210 (fish early lite stage toxicity test)
2-Aminoethanol 141-43-5	Value type	EC50
	Value	27.04 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Aminoethanol 141-43-5	Value type	EC50
	Value	2.8 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC10
	Value	0.7 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Aminoethanol 141-43-5	Value type	EC10
	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge, domestic
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptop 72244-98-5	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	5 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Benzyldimethylamine 103-83-3	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	0 - 2 %
	Method	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
2-Aminoethanol 141-43-5	Result	readily biodegradable
	Route of application	aerobic
	Degradability	> 80 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

Bioaccumulative potential / Mobility in soil:

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptop 72244-98-5	LogPow	1.2
	Temperature	20 °C
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Benzyldimethylamine 103-83-3	Bioconcentration factor (BCF)	> 2.1 - 22
	Exposure time	42 d
	Species	Cyprinus carpio
	Temperature	
	Method	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
Benzyldimethylamine 103-83-3	LogPow	1.98
	Temperature	
	Method	EU Method A.8 (Partition Coefficient)
2-Aminoethanol 141-43-5	LogPow	-1.91
	Temperature	25 °C

	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

Section 13. Disposal considerations

Product

Method of disposal:
Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages:
Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Class:	8
Packing group:	III
Classification code:	C7
Hazard ident. number:	80
UN no.:	2735
Label:	8
Technical name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Aliphatic amines)

Railroad transport RID:

Class:	8
Packing group:	III
Classification code:	C7
Hazard ident. number:	80
UN no.:	2735
Label:	8
Technical name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Aliphatic amines)

Inland water transport ADN:

Class:	8
Packing group:	III
Classification code:	C7
Hazard ident. number:	80
UN no.:	2735
Label:	8
Technical name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Aliphatic amines)

Marine transport IMDG:

Class:	8

Packing group:	III
UN no.:	2735
Label:	8
EmS:	F-A ,S-B
Seawater pollutant:	-
Proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Aliphatic amines)

Air transport IATA:

Class:	8
Packing group:	III
Packaging instructions (passenger):	852
Packaging instructions (cargo):	856
UN no.:	2735
Label:	8
Proper shipping name:	Amines, liquid, corrosive, n.o.s. (Aliphatic amines)

Section 15. Regulatory information

Regulatory Information:
Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

Global inventory status:

Regulatory list	Notification
TSCA	yes
AIIC	yes
DSL	yes
KECI (KR)	yes
IECSC	yes

Section 16. Other information

Disclaimer:
This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.
This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).