Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:
LOCTITE EA E-214HP 1KGEN

Other means of identification:
LOCTITE EA E-214HP 1KGEN

Product code:
IDH519104

Recommended use of the chemical and restrictions on use

Intended use:
One-part epoxy

Manufacturer/Importer/Distributor Representative Company

Henkel Thailand Ltd. The Offices at Centralworld,
35th Floor, 999/9 Rama 1 Rd.,
Kwang Patumwan, Khet Patumwan,
10330 Bangkok

Thailand

Phone: +66 (2209) 8000
Fax-no.: +66 (2209) 8008

E-mail address of person responsible for Safety Data Sheet:
ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents:
FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +662 209 8008

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category	Target organ
Self-reactive substances and mixtures	Type F	
Skin corrosion/irritation	Category 2	
Serious eye damage/eye irritation	Category 2A	
Skin sensitizer	Category 1	
Specific target organ toxicity - single exposure	Category 3	respiratory tract irritation
Chronic hazards to the aquatic environment	Category 2	

GHS label elements:

Hazard pictogram:



Signal word:
Warning

Hazard statement:
H242 Heating may cause a fire.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.

Precaution:

Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220 Keep away from clothing, strong acids, bases, heavy metal salts and other reducing substances, and combustible materials.
P234 Keep only in original packaging.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P391 Collect spillage.
Storage:
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P411 Store at temperatures not exceeding ....°C/....°F.
P420 Store separately.
Disposal:
P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	30- 60 %	Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Skin sensitizer 1A H317 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	10- 30 %	Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Skin sensitizer 1 H317 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
2-Propenoic acid, 2-methyl-, methyl ester, polymer with 1,3-butadiene, butyl 2-propenoate and ethenylbenzene 25101-28-4	10- 30 %	Skin corrosion/irritation 3 H316 Serious eye damage/eye irritation 2B H320 Skin sensitizer 1 H317
Dodecane-1-thiol 112-55-0	< 0.1 %	Skin corrosion/irritation 1 H314 Serious eye damage/eye irritation 1 H318 Skin sensitizer 1A H317 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410

Section 4. First aid measures

Inhalation:
Move to fresh air.
If breathing is difficult, give oxygen.
If not breathing, give artificial respiration.
If symptoms develop and persist, get medical attention.

Skin contact:
Immediately flush skin with plenty of water (using soap, if available).
Remove contaminated clothing and footwear.
If symptoms develop and persist, get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

Eye contact:
Immediately flush eyes with plenty of water for at least 15 minutes.
Get medical attention.

Ingestion:
DO NOT induce vomiting unless directed to do so by medical personnel.
Never give anything by mouth to an unconscious person.
Get medical attention.

Section 5. Fire fighting measures

Suitable extinguishing media:
Water spray (fog), foam, dry chemical or carbon dioxide.

Specific hazards arising from the chemical:
In case of fire, keep containers cool with water spray.
Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.

Special protection equipment and precautions for firefighters:
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products:
Oxides of carbon.
Oxides of nitrogen.
Acids.
Acrylic monomers.
Aldehydes.
Amines.
Ammonia.
Formaldehyde.
Hydrogen cyanide.
Isocyanates.
Phenolics.
Toxic fumes.
Irritating vapors.

Section 6. Accidental release measures

Personal precautions:
Avoid skin and eye contact.
Wear protective equipment.
Ensure adequate ventilation.
See advice in section 8

Environmental precautions:
Do not empty into drains / surface water / ground water.

Clean-up methods:
Remove all sources of ignition.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Scrape up spilled material and place in a closed container for disposal.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:
Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.
Use only with adequate ventilation.
Keep container closed.

Storage:
Store in tightly closed containers. In a cool/well-ventilated area.
Isolate from incompatible substances.
Keep away from sources of ignition and naked flames.
Protect from direct sunlight.
Refer to Technical Data Sheet.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

DODECYL MERCAPTAN 112-55-0	**Value type**	Time Weighted Average (TWA):
	ppm	0.1
	Remarks	ACGIH

Respiratory protection:
Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye protection:
Safety goggles or safety glasses with side shields.
Full face protection should be used if the potential for splashing or spraying of product exists.
Protective eye equipment should conform to EN166.

Body protection:
Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:
Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures:
The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Gray / Grey, Light Liquid, Paste
Odor:	Faint
Odor threshold (CA):	No data available.
pH:	No data available.
Melting point / freezing point:	No data available.
Specific gravity:	1.141.14
Boiling point:	No data available.
Flash point: (Setaflash Closed Cup; ASTM D3828 Method B)	> 93 °C (> 199.4 °F)
Evaporation rate:	No data available.

Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Density:	No data available.
Solubility:	No data available.
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content:	< 1 % < 10 g/l

Section 10. Stability and reactivity

Reactivity/Incompatible materials:
Acids.
Bases.
Amines.
Mercaptans.
Oxidizing agents.
Chemical stability:
Stable under recommended storage conditions.
Possibility of hazardous reactions:
Polymerization may occur at elevated temperature or in the presence of incompatible materials.
Conditions to avoid:
Keep away from heat, ignition sources and incompatible materials.
Note: Heating the epoxy resin in this product above 148.9 °C (300 °F) in the presence of air may cause slow oxidative decomposition. Above 260 °C (500 °F) polymerization of the epoxy resin may occur. Aliphatic polyamines can produce exothermic reactions with epoxy resins which in large masses can cause runaway polymerization and charring of the reactants. Fumes and vapors from these thermal and chemical decompositions vary widely in composition and toxicity. Do not breathe fumes.
Stable under normal conditions of storage and use.
Hazardous decomposition products:
Oxides of carbon.
Oxides of nitrogen.
Acids.
Acrylic monomers.
Aldehydes.
Amines.
Ammonia.
Formaldehyde.
Hydrogen cyanide.
Isocyanates.
Phenolics.
Toxic fumes.
Irritating vapors.

Section 11. Toxicological information

Health Effects:

Skin: Causes skin irritation.
May cause an allergic skin reaction.
Eyes: Causes serious eye irritation.
Symptoms of Overexposure**:** None known.

Acute oral toxicity:

Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 420 (Acute Oral Toxicity)
2-Propenoic acid, 2-methyl-, methyl ester, polymer with 1,3-butadiene, butyl 2-propenoate and ethenylbenzene 25101-28-4	Value type	LD50
	Value	> 10,000 mg/kg
	Species	mouse
	Method	not specified
Dodecane-1-thiol 112-55-0	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Dodecane-1-thiol 112-55-0	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Result	irritating
	Exposure time	4 h
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	irritating
	Exposure time	
	Species	
	Method	Weight of evidence
Dodecane-1-thiol 112-55-0	Result	Category 1C (corrosive)
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	irritating
	Exposure time	
	Species	
	Method	Weight of evidence

Respiratory or skin sensitization:

Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Result	Sub-Category 1A (sensitising)
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Dodecane-1-thiol 112-55-0	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Result	positive
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	rat
	Method	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified
Dodecane-1-thiol 112-55-0	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Dodecane-1-thiol 112-55-0	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Dodecane-1-thiol 112-55-0	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity:

Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Result	NOAEL=250 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	13 wdaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	NOAEL=50 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	14 wdaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H411 Toxic to aquatic life with long lasting effects.

Toxicity:

Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Value type	LC50
	Value	5.7 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Ide, silver or golden orfe (Leuciscus idus)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Value type	EC50
	Value	3.5 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Value type	EC50
	Value	9.4 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Value type	IC50
	Value	> 100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	LC50
	Value	1.75 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	EC50
	Value	1.7 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	EC50
	Value	> 11 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	4.2 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	IC50
	Value	> 100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge, industrial
	Method	other guideline:
Dodecane-1-thiol 112-55-0	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	EPA OTS 797.1400 (Fish Acute Toxicity Test)

Dodecane-1-thiol 112-55-0	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Dodecane-1-thiol 112-55-0	Value type	EC50
	Value	0.0145 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC10
	Value	0.0145 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)

Persistence and degradability:

Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	5 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	5 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Dodecane-1-thiol 112-55-0	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	39.2 %
	Method	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	Bioconcentration factor (BCF)	31
	Exposure time	
	Species	not specified
	Temperature	
	Method	not specified
Phenol polymer with formaldehyde, glycidyl ether 28064-14-4	LogPow	3.242
	Temperature	
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	LogPow	3.242
	Temperature	25 °C
	Method	EU Method A.8 (Partition Coefficient)
Dodecane-1-thiol 112-55-0	LogPow	> 6.5
	Temperature	25 °C
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

Section 13. Disposal considerations

Product

Method of disposal:
Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages:
Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Class:	4.2
Packing group:	II
Classification code:	S1
Hazard ident. number:	30
UN no.:	3183
Label:	4.2
Technical name:	SELF-HEATING LIQUID, ORGANIC, N.O.S. (Amino compound)

Railroad transport RID:

Class:	4.2
Packing group:	II
Classification code:	S1
Hazard ident. number:	30
UN no.:	3183
Label:	4.2
Technical name:	SELF-HEATING LIQUID, ORGANIC, N.O.S. (Amino compound)

Inland water transport ADN:

Class:	4.2
Packing group:	II
Classification code:	S1
Hazard ident. number:	30
UN no.:	3183
Label:	4.2
Technical name:	SELF-HEATING LIQUID, ORGANIC, N.O.S. (Amino compound)

Marine transport IMDG:

Class:	4.2
Packing group:	II
UN no.:	3183
Label:	4.2
EmS:	F-A ,S-J
Seawater pollutant:	Marine pollutant
Proper shipping name:	SELF-HEATING LIQUID, ORGANIC, N.O.S. (Amino compound,Epoxy resin)

Air transport IATA:

Class:	4.2
Packing group:	II
Packaging instructions (passenger):	462
Packaging instructions (cargo):	464
UN no.:	3183
Label:	4.2
Proper shipping name:	Self-heating liquid, organic, n.o.s. (Amino compound)

Section 15. Regulatory information

Regulatory Information:
Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

Global inventory status:

Regulatory list	Notification
TCSI	yes
TSCA	yes
DSL	yes
ENCS (JP)	yes
ISHL (JP)	yes
KECI (KR)	yes
IECSC	yes
NZIOC	yes

Section 16. Other information

Disclaimer:
This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.
This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).