Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:
LOCTITE ECCOBOND FP4530 10CC

Other means of identification:
LOCTITE ECCOBOND FP4530 10CC

Product code:
IDH2453383
Recommended use of the chemical and restrictions on use

Intended use:
1-c- epoxide adhesive
Manufacturer/Importer/Distributor Representative Company

Henkel Thailand Ltd. The Offices at Centralworld,
35th Floor, 999/9 Rama 1 Rd.,
Kwang Patumwan, Khet Patumwan,
10330 Bangkok

Thailand

Phone: +66 (2209) 8000
Fax-no.: +66 (2209) 8008

E-mail address of person responsible for Safety Data Sheet:
ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents:
FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +662 209 8008

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Germ cell mutagenicity	Category 2
Chronic hazards to the aquatic environment	Category 3

GHS label elements:

Hazard pictogram:



Signal word:
Danger

Hazard statement:
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341 Suspected of causing genetic defects.
H412 Harmful to aquatic life with long lasting effects.

Precaution:

Prevention:
P201 Obtain special instructions before use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P284 [In case of inadequate ventilation] wear respiratory protection.

Response:
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor.
P362+P364 Take off contaminated clothing and wash it before reuse.

Disposal:
P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Aluminium oxide - non fibrous form 1344-28-1	30- 60 %	
hexahydromethylphthalic anhydride 25550-51-0	10- 30 %	Serious eye damage/eye irritation 1 H318 Respiratory sensitizer 1 H334 Skin sensitizer 1 H317
6-glycidyloxynapht-1-yl oxymethyloxirane 27610-48-6	10- 30 %	Acute toxicity 5; Oral H303 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Skin sensitizer 1 H317 Germ cell mutagenicity 2 H341 Acute hazards to the aquatic environment 3 H402 Chronic hazards to the aquatic environment 3 H412
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	1- 10 %	Skin corrosion/irritation 2 H315 Skin sensitizer 1A H317 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	1- 10 %	Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Skin sensitizer 1 H317 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	0.1- 1 %	Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Skin sensitizer 1 H317 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411

Section 4. First aid measures

Inhalation:
Move to fresh air, consult doctor if complaint persists.

Skin contact:
Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If necessary, see a dermatologist.
Seek medical advice.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.
Seek medical advice.

Indication of immediate medical attention and special treatment needed:
See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:
Foam, extinguishing powder, carbon dioxide.
Fine water spray

Improper extinguishing media:
High pressure waterjet

Specific hazards arising from the chemical:
Danger of decomposition if exposed to heat.
In case of fire, keep containers cool with water spray.

Special protection equipment and precautions for firefighters:
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products:
Oxides of aluminum.
See section 10.

Section 6. Accidental release measures

Personal precautions:
Avoid contact with skin and eyes.
Wear protective equipment.
Ensure adequate ventilation.

Environmental precautions:
Do not empty into drains / surface water / ground water.

Clean-up methods:
Remove mechanically.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:
Ensure good ventilation/suction at the workplace.
Extract when the product is heated.
See advice in section 8
Do not spray onto flames or red-hot objects.
Keep away from sources of ignition - no smoking.

Storage:
Store in sealed original container.
Protect against contamination.
Store in a cool, dry place.
Ensure that storage and workrooms are adequately ventilated.
Must be stored in a room with spill collection facilities.
Keep away from heat and direct sunlight.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

ALUMINUM METAL AND INSOLUBLE COMPOUNDS, RESPIRABLE FRACTION 1344-28-1	**Value type**	Time Weighted Average (TWA):
	mg/m³	1
	Remarks	ACGIH
ALPHA-ALUMINA, RESPIRABLE DUST 1344-28-1	**Value type**	Time Weighted Average (TWA):
	mg/m³	5
	Remarks	TH OEL
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles 1344-28-1	**Value type**	Time Weighted Average (TWA):
	mg/m³	3
	Remarks	ACGIH
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles 1344-28-1	**Value type**	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH
ALPHA-ALUMINA, INHALABLE DUST 1344-28-1	**Value type**	Time Weighted Average (TWA):
	mg/m³	15
	Remarks	TH OEL

Respiratory protection:
Suitable breathing mask when there is inadequate ventilation.
Suitable respiratory protection:
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Goggles which can be tightly sealed.
and/or
facial protection
Protective eye equipment should conform to EN166.

Body protection:
Wear protective equipment.
Protective clothing that covers arms and legs.
apron
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:
Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures:
The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Light blue liquid
Odor:	mild
Odor threshold (CA):	No data available.
pH:	Not available.
Melting point / freezing point:	Not applicable, Product is a liquid
Specific gravity:	1.8
Boiling point:	No data available.
Flash point: (Open cup)	> 121.11 °C (> 250 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure:	Not available.
Vapor density:	Not available.
Density:	1.8 g/cm3
Solubility:	No data available.
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content:	No data available.

Section 10. Stability and reactivity

Reactivity/Incompatible materials:
Reacts with alcohols and amines.
Reacts with oxidants, acids and lyes
Polymerization may occur at elevated temperature or in the presence of incompatible materials.
Chemical stability:
Stable under recommended storage conditions.

Conditions to avoid:
Danger of decomposition if exposed to heat.
Do not heat mixed adhesive unless you plan to use immediately.
Failure to observe these precautions may result in excessive heat build-up causing an exotherm.
Avoid moisture.
Hazardous decomposition products:
Hydrocarbons
Irritating vapors.
At higher temperature carbon oxides and nitrogen oxides may be generated.
May produce fumes when heated to decomposition. Fumes may contain carbon monoxide and other toxic fumes.
See section 5.

Section 11. Toxicological information

General toxicological information: Possible risk of irreversible effects.

Dermal toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg
Method: Calculation method

Symptoms of Overexposure**:** EYE: Irritation, conjunctivitis.
SKIN: Redness, inflammation.
SKIN: Rash, Urticaria.
RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

Acute oral toxicity:

Aluminium oxide - non fibrous form 1344-28-1	Value type	LD50
	Value	> 10,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
hexahydromethylphthalic anhydride 25550-51-0	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	EU Method B.1 tris (Acute Oral Toxicity)
6-glycidyloxynapht-1-yl oxymethyloxirane 27610-48-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	EPA OTS 798.1175 (Acute Oral Toxicity)
6-glycidyloxynapht-1-yl oxymethyloxirane 27610-48-6	Value type	Acute toxicity estimate (ATE)
	Value	2,500 mg/kg
	Species	
	Method	Expert judgement
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 420 (Acute Oral Toxicity)

Acute dermal toxicity:

hexahydromethylphthalic anhydride 25550-51-0	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
6-glycidyloxynapht-1-yl oxymethyloxirane 27610-48-6	Value type	LD50
	Value	> 1,000 - < 2,000 mg/kg
	Species	rat
	Method	EPA OTS 798.1100 (Acute Dermal Toxicity)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Aluminium oxide - non fibrous form 1344-28-1	Result	not irritating
	Exposure time	24 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
hexahydromethylphthalic anhydride 25550-51-0	Result	moderately irritating
	Exposure time	24 h
	Species	rabbit
	Method	other guideline:
6-glycidyloxynapht-1-yl oxymethyloxirane 27610-48-6	Result	irritating
	Exposure time	
	Species	rabbit
	Method	EPA OTS 798.4470 (Acute Dermal Irritation)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	irritating
	Exposure time	4 h
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	irritating
	Exposure time	
	Species	
	Method	Weight of evidence

Serious eye damage/irritation:

Aluminium oxide - non fibrous form 1344-28-1	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
6-glycidyloxynapht-1-yl oxymethyloxirane 27610-48-6	Result	irritating
	Exposure time	
	Species	rabbit
	Method	EPA OTS 798.4500 (Acute Eye Irritation)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	irritating
	Exposure time	
	Species	
	Method	Weight of evidence

Respiratory or skin sensitization:

Aluminium oxide - non fibrous form 1344-28-1	Result	not sensitising
	Test type	Draize Test
	Species	guinea pig
	Method	Landsteiner & Jacobs Method
6-glycidyloxynapht-1-yl oxymethyloxirane 27610-48-6	Result	sensitising
	Test type	Buehler test
	Species	guinea pig
	Method	EPA OTS 798.4100 (Skin Sensitisation)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	Sub-Category 1A (sensitising)
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

Aluminium oxide - non fibrous form 1344-28-1	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Aluminium oxide - non fibrous form 1344-28-1	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Aluminium oxide - non fibrous form 1344-28-1	Result	positive without metabolic activation
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Aluminium oxide - non fibrous form 1344-28-1	Result	positive without metabolic activation
	Type of study / Route of administration	in vitro mammalian cell micronucleus test
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Aluminium oxide - non fibrous form 1344-28-1	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	rat
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Aluminium oxide - non fibrous form 1344-28-1	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	rat
	Method	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
hexahydromethylphthalic anhydride 25550-51-0	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
hexahydromethylphthalic anhydride 25550-51-0	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
hexahydromethylphthalic anhydride 25550-51-0	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
6-glycidyloxynapht-1-yl oxymethyloxirane 27610-48-6	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
6-glycidyloxynapht-1-yl oxymethyloxirane 27610-48-6	Result	positive
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
6-glycidyloxynapht-1-yl oxymethyloxirane 27610-48-6	Result	positive
	Type of study / Route of administration	intraperitoneal
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	positive
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Reaction mass bisphenol-F-	Result	negative

(epichlorhydrin) 9003-36-5	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	rat
	Method	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified

Repeated dose toxicity:

Aluminium oxide - non fibrous form 1344-28-1	Result	NOAEL=>= 0.075 mg/l
	Route of application	inhalation: dust
	Exposure time / Frequency of treatment	6 months6 h/d, 5 d/week
	Species	rat
	Method	equivalent or similar to OECD Guideline 452 (Chronic Toxicity Studies)
Aluminium oxide - non fibrous form 1344-28-1	Result	NOAEL=113.36 mg/kg
	Route of application	oral: drinking water
	Exposure time / Frequency of treatment	364 dAd libitum (daily)
	Species	rat
	Method	OECD Guideline 452 (Chronic Toxicity Studies)
hexahydromethylphthalic anhydride 25550-51-0	Result	NOAEL=450 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	28 donce a day, 7 days a week
	Species	rat
	Method	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	NOAEL=250 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	13 wdaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	NOAEL=50 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	14 wdaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H412 Harmful to aquatic life with long lasting effects.

Toxicity:

Aluminium oxide - non fibrous form 1344-28-1	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Salmo trutta
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Aluminium oxide - non fibrous form 1344-28-1	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Aluminium oxide - non fibrous form 1344-28-1	Value type	NOEC
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	EC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Aluminium oxide - non fibrous form 1344-28-1	Value type	EC0
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Bacteria
	Exposure time	
	Species	not specified
	Method	not specified
hexahydromethylphthalic anhydride 25550-51-0	Value type	LC50
	Value	500 mg/l
	Acute Toxicity Study	Fish
	Exposure time	48 h
	Species	Oryzias latipes
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
hexahydromethylphthalic anhydride 25550-51-0	Value type	EC50
	Value	> 100 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
hexahydromethylphthalic anhydride 25550-51-0	Value type	EC50
	Value	135 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	32 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
hexahydromethylphthalic anhydride 25550-51-0	Value type	EC20
	Value	95.3 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge, domestic
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Value type	LC50
	Value	5.7 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus

	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Value type	EC50
	Value	2.55 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Value type	EC50
	Value	1.8 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Value type	IC50
	Value	> 100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge, industrial
	Method	other guideline:
Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	Value type	EC50
	Value	1.9 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	Value type	EC50
	Value	1.8 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	LC50
	Value	1.75 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	EC50
	Value	1.7 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	EC50
	Value	> 11 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	4.2 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Value type	IC50
	Value	> 100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge, industrial
	Method	other guideline:

Persistence and degradability:

hexahydromethylphthalic anhydride 25550-51-0	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	2 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	0 %
	Method	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	0 %
	Method	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	5 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

Bioaccumulative potential / Mobility in soil:

hexahydromethylphthalic anhydride 25550-51-0	Bioconcentration factor (BCF)	11.12
	Exposure time	
	Species	calculated
	Temperature	
	Method	QSAR (Quantitative Structure Activity Relationship)
hexahydromethylphthalic anhydride 25550-51-0	LogPow	2.59
	Temperature	25 °C
	Method	QSAR (Quantitative Structure Activity Relationship)
Reaction mass bisphenol-F-(epichlorhydrin) 9003-36-5	LogPow	2.7 - 3.6
	Temperature	
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Formaldehyde, polymer reaction products with 1-chloro-2,3-epoxypropane and phenol 9003-36-5	LogPow	> 2.7 - 3.6
	Temperature	
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	LogPow	3.242
	Temperature	25 °C
	Method	EU Method A.8 (Partition Coefficient)

Section 13. Disposal considerations

Product

Method of disposal:
Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages:
Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:
Not dangerous goods

Railroad transport RID:
Not dangerous goods

Inland water transport ADN:
Not dangerous goods

Marine transport IMDG:
Not dangerous goods

Air transport IATA:
Not dangerous goods

Section 15. Regulatory information

Regulatory Information:
Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

Global inventory status:

Regulatory list	Notification
TCSI	yes
TSCA	yes
ENCS (JP)	yes
ISHL (JP)	yes
IECSC	yes

Section 16. Other information

Disclaimer:
This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.
This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).