Safety Data Sheet

LOCTITE MR 5923 TB960G

SDS No. : 153785
V001.8
Revision: 15.01.2025
printing date: 04.11.2026

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:
LOCTITE MR 5923 TB960G

Other means of identification:
LOCTITE MR 5923 TB960G

Product code:
IDH235152

Recommended use of the chemical and restrictions on use

Intended use:
Sealant

Manufacturer/Importer/Distributor Representative Company

Henkel Thailand Ltd. The Offices at Centralworld,
35th Floor, 999/9 Rama 1 Rd.,
Kwang Patumwan, Khet Patumwan,
10330 Bangkok

Thailand

Phone: +66 (2209) 8000
Fax-no.: +66 (2209) 8008

E-mail address of person responsible for Safety Data Sheet:
ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents:
FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +662 209 8008

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category	Target organ
Flammable liquids	Category 2	
Serious eye damage/eye irritation	Category 2	
Skin sensitizer	Category 1	
Specific target organ toxicity - single exposure	Category 3	Central nervous system

GHS label elements:

Hazard pictogram:



Signal word:
Danger

Hazard statement:
H225 Highly flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precaution:

Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
Storage:
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
Disposal:
P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
rosin 8050-09-7	10- 30 %	Acute toxicity 5; Oral H303 Skin sensitizer 1 H317
Propan-2-ol 67-63-0	10- 30 %	Flammable liquids 2 H225 Serious eye damage/eye irritation 2A H319 Specific target organ toxicity - single exposure 3 H336 Aspiration hazard 2 H305
Talc 14807-96-6	10- 30 %	

Section 4. First aid measures

Inhalation:
Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:
Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Indication of immediate medical attention and special treatment needed:
See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:
Foam, extinguishing powder, carbon dioxide.

Improper extinguishing media:
High pressure waterjet

Specific hazards arising from the chemical:
Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.
Formation of toxic gases is possible during heating or in fires.

Special protection equipment and precautions for firefighters:
Wear self-contained breathing apparatus.

Hazardous combustion products:
Oxides of carbon, oxides of nitrogen, irritating organic vapors.

Additional fire fighting advice:
In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:
Remove sources of ignition.
Ensure adequate ventilation.
Avoid skin and eye contact.
Wear protective equipment.
See advice in section 8

Environmental precautions:
Do not empty into drains / surface water / ground water.

Clean-up methods:
Wipe up using absorbent material.
Store in a partly filled, closed container until disposal.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:
Keep away from sources of ignition - no smoking.
Vapours should be extracted to avoid inhalation.
Use only in well-ventilated areas.
Avoid skin and eye contact.
See advice in section 8

Storage:
Store in a cool, dry place.
Do not store near sources of heat or ignition, or reactive materials.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

2-PROPANOL 67-63-0	**Value type**	Time Weighted Average (TWA):
	ppm	200
	Remarks	ACGIH
ISOPROPYL ALCOHOL (IPA) 67-63-0	**Value type**	Time Weighted Average (TWA):
	ppm	400
	Remarks	TH OEL
2-PROPANOL 67-63-0	**Value type**	Short Term Exposure Limit (STEL):
	ppm	400
	Remarks	ACGIH
TALC, CONTAINING NO ASBESTOS FIBERS, RESPIRABLE FRACTION 14807-96-6	**Value type**	Time Weighted Average (TWA):
	mg/m³	2
	Remarks	ACGIH The value is for particulate matter containing no asbestos and <1% crystalline silica.
TALC CONTAINING NO ASBESTOS FIBRES, RESPIRABLE DUST 14807-96-6	**Value type**	Time Weighted Average (TWA):
	mg/m³	2
	Remarks	TH OEL

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Body protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:
Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures:
The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Brown liquid
Odor:	Alcoholic
Odor threshold (CA):	No data available.
pH:	Not applicable, Product is non-soluble (in water).
Melting point / freezing point:	Not applicable, Product is a liquid
Specific gravity:	1.12
Boiling point:	> 82 °C (> 179.6 °F)
Flash point: (None)	15 °C (59 °F)
Evaporation rate:	7.7 (Ether = 1)
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure: (; 20 °C (68 °F))	33 mm hg
Vapor density:	2.07 (Air = 1)
Density:	1.1 g/cm3
Solubility:	Partially soluble
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content: (2010/75/EC)	25 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials:
Strong oxidizing agents.
Chemical stability:
Stable under recommended storage conditions.

Conditions to avoid:
Stable under normal conditions of storage and use.
Heat, flames, sparks and other sources of ignition.
Hazardous decomposition products:
carbon oxides.
aldehydes

Section 11. Toxicological information

Symptoms of Overexposure**:** SKIN: Rash, Urticaria.
EYE: Irritation, conjunctivitis.
Vapors may cause drowsiness and dizziness.

Acute oral toxicity:

rosin 8050-09-7	Value type	LD50
	Value	2,800 mg/kg
	Species	rat
	Method	not specified
Propan-2-ol 67-63-0	Value type	LD50
	Value	5,840 mg/kg
	Species	rat
	Method	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Talc 14807-96-6	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 423 (Acute Oral toxicity)

Acute inhalative toxicity:

Talc 14807-96-6	Value type	LC50
	Value	> 2.1 mg/l
	Exposure time	4 h
	Species	rat
	Method	OECD Guideline 403 (Acute Inhalation Toxicity)

Acute dermal toxicity:

rosin 8050-09-7	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Propan-2-ol 67-63-0	Value type	LD50
	Value	12,870 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)
Talc 14807-96-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

rosin 8050-09-7	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Propan-2-ol 67-63-0	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Talc 14807-96-6	Result	slightly irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

rosin 8050-09-7	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Propan-2-ol 67-63-0	Result	Category 2A (irritating to eyes)
	Exposure time	
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Talc 14807-96-6	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Propan-2-ol 67-63-0	Result	not sensitising
	Test type	Buehler test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)
Talc 14807-96-6	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

rosin 8050-09-7	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Propan-2-ol 67-63-0	Result	negative
	Type of study / Route of administration	intraperitoneal
	Metabolic activation / Exposure time	
	Species	mouse
	Method	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Talc 14807-96-6	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Talc 14807-96-6	Result	negative
	Type of study / Route of administration	in vitro mammalian cell transformation assay
	Metabolic activation / Exposure time	without
	Method	equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Talc 14807-96-6	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	rat
	Method	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)

Repeated dose toxicity:

Propan-2-ol 67-63-0	Result	
	Route of application	inhalation: vapour
	Exposure time / Frequency of treatment	104 w6 h/d, 5 d/w
	Species	rat
	Method	OECD Guideline 451 (Carcinogenicity Studies)
Talc 14807-96-6	Result	NOAEL=100 mg/kg
	Route of application	oral: feed
	Exposure time / Frequency of treatment	101 d7 d/w
	Species	rat
	Method	equivalent or similar to OECD Guideline 452 (Chronic Toxicity Studies)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity:

Toxicity:

rosin 8050-09-7	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
rosin 8050-09-7	Value type	EL50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
rosin 8050-09-7	Value type	EL50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOELR
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
rosin 8050-09-7	Value type	EC20
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge of a predominantly domestic sewage
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Propan-2-ol 67-63-0	Value type	LC50
	Value	> 9,640 - 10,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propan-2-ol 67-63-0	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)

	Value type	NOEC
	Value	1,000 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	activated sludge
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Talc 14807-96-6	Value type	LC50
	Value	Toxicity > Water solubility
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)

Persistence and degradability:

rosin 8050-09-7	Result	readily biodegradable
	Route of application	aerobic
	Degradability	71 %
	Method	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Propan-2-ol 67-63-0	Result	readily biodegradable
	Route of application	aerobic
	Degradability	70 - 84 %
	Method	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)

Bioaccumulative potential / Mobility in soil:

rosin 8050-09-7	LogPow	> 3 - 6.2
	Temperature	
	Method	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Propan-2-ol 67-63-0	LogPow	0.05
	Temperature	
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Talc 14807-96-6	LogPow	-9.4
	Temperature	25 °C
	Method	QSAR (Quantitative Structure Activity Relationship)

Section 13. Disposal considerations

Product

Method of disposal:
Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages:
Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Class:	3
Packing group:	II
Classification code:	F1
Hazard ident. number:	33
UN no.:	1866
Label:	3
Technical name:	RESIN SOLUTION
Additional information:	Special provision 640D

Railroad transport RID:

Class:	3
Packing group:	II
Classification code:	F1
Hazard ident. number:	33
UN no.:	1866
Label:	3
Technical name:	RESIN SOLUTION
Additional information:	Special provision 640D

Inland water transport ADN:

Class:	3
Packing group:	II
Classification code:	F1
Hazard ident. number:	33
UN no.:	1866
Label:	3
Technical name:	RESIN SOLUTION
Additional information:	Special provision 640D

Marine transport IMDG:

Class:	3
Packing group:	II
UN no.:	1866
Label:	3
EmS:	F-E ,S-E
Seawater pollutant:	-
Proper shipping name:	RESIN SOLUTION

Air transport IATA:

Class:	3
Packing group:	II
Packaging instructions (passenger):	353
Packaging instructions (cargo):	364
UN no.:	1866
Label:	3
Proper shipping name:	Resin solution

Section 15. Regulatory information

Regulatory Information:
Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
ENCS (JP)	yes
IECSC	yes
NZIOC	yes
TCSI	yes
PICCS (PH)	yes
EINECS	yes

Section 16. Other information

Disclaimer:
This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.
This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).