Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:
LOCTITE SF 7388 150ML SE/FI

Other means of identification:
LOCTITE SF 7388 150ML SE/FI

Product code:
IDH230043

Recommended use of the chemical and restrictions on use

Intended use:
activator

Identification of manufacturer, importer or distributor

Manufacturer: Henkel Ireland Ltd., Dublin / Tallaght (Manufacturing & Research), Tallaght Business Park Whitestown, Tallaght, Dublin 24, Ireland. Phone: 00 353 1 404 6444 Fax: 00 353 1 459 9298

Importer: Henkel Thailand Ltd The Offices at Centralworld, 35th Floor, 999/9 Rama 1 Rd, Kwang Patumwan, Khet Patumwan, Bangkok 10330, Thailand. Phone : + 6622098000 Fax : +6622098008

E-mail address of person responsible for Safety Data Sheet:
ap-ua-psra.sea@henkel.com

Emergency Telephone for Chemical Accidents:
FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +662 209 8008

Section 2. Hazards identification

GHS Classification:

Hazard Class	Hazard Category	Route of Exposure	Target organ
Flammable aerosols	Category 1		
Acute toxicity	Category 4	Oral	
Skin corrosion/irritation	Category 2		
Serious eye damage/eye irritation	Category 2		
Specific target organ toxicity - single exposure	Category 3		Central nervous system
Acute hazards to the aquatic environment	Category 1		
Chronic hazards to the aquatic environment	Category 1		

GHS label elements:

Hazard pictogram:



Signal word:
Danger

Hazard statement:
H222 Extremely flammable aerosol.
H229 Pressurized container: May burst if heated.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.

Precaution:

Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:
P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor/… if you feel unwell.
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.

Storage:
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal:
P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
acetone 67-64-1	30- 60 %	Flammable liquids 2 H225 Serious eye damage/eye irritation 2A H319 Specific target organ toxicity - single exposure 3 H336
3,5-Diethyl-1,2-dihydro-1-phenyl-2-propylpyridine 34562-31-7	30- 60 %	Acute toxicity 4; Oral H302 Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2B H320 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	30- 60 %	Flammable liquids 2 H225 Acute toxicity 5; Inhalation H333 Skin corrosion/irritation 2 H315 Aspiration hazard 1 H304 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
propane 74-98-6	1- 10 %	Flammable gases 1 H220 Gases under pressure
butane 106-97-8	1- 10 %	Flammable gases 1 H220 Gases under pressure Compr. Gas H280

Section 4. First aid measures

Inhalation:
Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:
Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Indication of immediate medical attention and special treatment needed:
See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

Improper extinguishing media:
High pressure waterjet

Specific hazards arising from the chemical:
Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.

Special protection equipment and precautions for firefighters:
Wear self-contained breathing apparatus.

Hazardous combustion products:
Oxides of carbon, oxides of nitrogen, irritating organic vapors.

Additional fire fighting advice:
In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:
Avoid skin and eye contact.
Ensure adequate ventilation.
Wear protective equipment.
See advice in section 8

Environmental precautions:
Do not empty into drains / surface water / ground water.

Clean-up methods:
For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:
Keep away from sources of ignition - no smoking.
Vapours should be extracted to avoid inhalation.
Use only in well-ventilated areas.
Avoid skin and eye contact.
See advice in section 8

Storage:
Store in a cool, dry place.
Do not store near sources of heat or ignition, or reactive materials.
Refer to Technical Data Sheet.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

ACETONE 67-64-1	**Value type**	Time Weighted Average (TWA):
	ppm	250
	Remarks	ACGIH
ACETONE 67-64-1	**Value type**	Time Weighted Average (TWA):
	ppm	1,000
	Remarks	TH OEL
ACETONE 67-64-1	**Value type**	Short Term Exposure Limit (STEL):
	ppm	500
	Remarks	ACGIH
Hexane (Commercial, <54% n-Hexane) 64742-49-0	**Value type**	Time Weighted Average (TWA):
	ppm	100
	Remarks	ACGIH
Hexane (Commercial, <54% n-Hexane) 64742-49-0	**Value type**	Skin designation:
	Remarks	ACGIH Danger of cutaneous absorption
PROPANE 74-98-6	**Remarks**	ACGIH D: Simple asphyxiant, EX: Explosion hazard
Butane, all isomers 106-97-8	**Value type**	Short Term Exposure Limit (STEL):
	ppm	1,000
	Remarks	ACGIH EX: Explosion hazard

Respiratory protection:
Do not inhale vapors and fumes.
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Body protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:
Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

General protection and hygiene measures:
The workplace should be equipped with an emergency shower and eye-rinsing facility.

Hygienic measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

Section 9. Physical and chemical properties

Appearance:	Amber aerosol
Odor:	pungent
Odor threshold (CA):	No data available.
pH:	Not applicable
Melting point / freezing point:	Not applicable, Product is a liquid
Specific gravity:	No data available.
Boiling point:	-44.0 °C (-47.2 °F)
Flash point:	-97.00 °C (-142.6 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	0.6 %(V)
Upper explosive limit:	13 %(V)
Vapor pressure: (; 20 °C (68 °F))	8300 mbar
Vapor density:	Heavier than air
Density:	0.7970 g/cm3
Solubility:	Not miscible
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC content: (2010/75/EC)	73 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials:
Strong oxidizing agents.
Chemical stability:
Stable under recommended storage conditions.
Conditions to avoid:
No decomposition if used according to specifications.
Heat, flames, sparks and other sources of ignition.
Hazardous decomposition products:
None if used for intended purpose.

Section 11. Toxicological information

Oral toxicity: Acute toxicity estimate (ATE) : 1,251 mg/kg
Method: Calculation method

Symptoms of Overexposure**:** INGESTION: Nausea, vomiting, diarrhea, abdominal pain.

SKIN: Redness, inflammation.
EYE: Irritation, conjunctivitis.
Vapors may cause drowsiness and dizziness.

Acute oral toxicity:

acetone 67-64-1	Value type	LD50
	Value	5,800 mg/kg
	Species	rat
	Method	not specified
3,5-Diethyl-1,2-dihydro-1-phenyl-2-propylpyridine 34562-31-7	Value type	LD50
	Value	> 500 mg/kg
	Species	rat
	Method	other guideline:
3,5-Diethyl-1,2-dihydro-1-phenyl-2-propylpyridine 34562-31-7	Value type	Acute toxicity estimate (ATE)
	Value	501 mg/kg
	Species	
	Method	Expert judgement
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Value type	LD50
	Value	> 5,840 mg/kg
	Species	rat
	Method	not specified

Acute inhalative toxicity:

acetone 67-64-1	Value type	LC50
	Value	76 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Value type	LC50
	Value	> 23.3 mg/l
	Exposure time	4 h
	Species	rat
	Method	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Value type	Acute toxicity estimate (ATE)
	Value	23.31 mg/l
	Exposure time	
	Species	
	Method	Expert judgement
propane 74-98-6	Value type	LC50
	Value	> 800000 ppm
	Exposure time	15 min
	Species	rat
	Method	not specified
butane 106-97-8	Value type	LC50
	Value	274200 ppm
	Exposure time	4 h
	Species	rat
	Method	not specified

Acute dermal toxicity:

acetone 67-64-1	Value type	LD50
	Value	> 15,688 mg/kg
	Species	rabbit
	Method	Draize Test
3,5-Diethyl-1,2-dihydro-1-phenyl-2-propylpyridine 34562-31-7	Value type	LD50
	Value	> 1,000 mg/kg
	Species	rabbit
	Method	other guideline:
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Value type	LD50
	Value	> 2,800 mg/kg
	Species	rat
	Method	other guideline:

Skin corrosion/irritation:

acetone 67-64-1	Result	not irritating
	Exposure time	
	Species	guinea pig
	Method	not specified
3,5-Diethyl-1,2-dihydro-1-phenyl-2-propylpyridine 34562-31-7	Result	irritating
	Exposure time	4 h
	Species	rabbit
	Method	EPA OTS 798.4470 (Acute Dermal Irritation)
3,5-Diethyl-1,2-dihydro-1-phenyl-2-propylpyridine 34562-31-7	Result	not corrosive
	Exposure time	
	Species	Corrositex Biobarrier Membrane (reconstituted collagen matrix)
	Method	OECD Guideline 435 (In Vitro Membrane Barrier Test Method for Skin Corrosion)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Result	irritating
	Exposure time	4 h
	Species	rabbit
	Method	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

acetone 67-64-1	Result	irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
3,5-Diethyl-1,2-dihydro-1-phenyl-2-propylpyridine 34562-31-7	Result	Category 2B (mildly irritating to eyes)
	Exposure time	
	Species	rabbit
	Method	EPA OTS 798.4500 (Acute Eye Irritation)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	FDA Guideline

Respiratory or skin sensitization:

acetone 67-64-1	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	not specified
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

acetone 67-64-1	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
acetone 67-64-1	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
acetone 67-64-1	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
acetone 67-64-1	Result	negative
	Type of study / Route of administration	oral: drinking water
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified
propane 74-98-6	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
propane 74-98-6	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
propane 74-98-6	Result	negative
	Type of study / Route of administration	
	Metabolic activation / Exposure time	
	Species	Drosophila melanogaster
	Method	not specified
propane 74-98-6	Result	negative
	Type of study / Route of administration	inhalation: gas
	Metabolic activation / Exposure time	
	Species	rat
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
butane 106-97-8	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
butane 106-97-8	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
butane 106-97-8	Result	negative
	Type of study / Route of administration	inhalation: gas
	Metabolic activation / Exposure time	
	Species	rat
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity:

acetone 67-64-1	Result	NOAEL=900 mg/kg
	Route of application	oral: drinking water
	Exposure time / Frequency of treatment	13 wdaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
propane 74-98-6	Result	
	Route of application	inhalation: gas
	Exposure time / Frequency of treatment	28 d6 h/d, 7 d/w
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
butane 106-97-8	Result	
	Route of application	inhalation: gas
	Exposure time / Frequency of treatment	28 d6 h/d
	Species	rat
	Method	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H410 Very toxic to aquatic life with long lasting effects.

Toxicity:

acetone 67-64-1	Value type	LC50
	Value	8,120 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
acetone 67-64-1	Value type	EC50
	Value	8,800 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia pulex
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
acetone 67-64-1	Value type	NOEC
	Value	530 mg/l
	Acute Toxicity Study	Algae
	Exposure time	8 d
	Species	Microcystis aeruginosa
	Method	DIN 38412-09
acetone 67-64-1	Value type	EC10
	Value	1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	Pseudomonas putida
	Method	DIN 38412, part 27 (Bacterial oxygen consumption test)
3,5-Diethyl-1,2-dihydro-1-phenyl-2-propylpyridine 34562-31-7	Value type	EC50
	Value	0.023 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h

	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3,5-Diethyl-1,2-dihydro-1-phenyl-2-propylpyridine 34562-31-7	Value type	EC50
	Value	0.0431 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	0.017 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Value type	LL50
	Value	> 13.4 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Value type	EC50
	Value	3 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Value type	EL50
	Value	29 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOELR
	Value	6.3 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
butane 106-97-8	Value type	LC50
	Value	27.98 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	
	Method	QSAR (Quantitative Structure Activity Relationship)
butane 106-97-8	Value type	EC50
	Value	14.22 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	
	Method	QSAR (Quantitative Structure Activity Relationship)
butane 106-97-8	Value type	EC50
	Value	7.71 mg/l
	Acute Toxicity Study	Algae
	Exposure time	96 h
	Species	
	Method	QSAR (Quantitative Structure Activity Relationship)

Persistence and degradability:

acetone 67-64-1	Result	readily biodegradable
	Route of application	aerobic
	Degradability	81 - 92 %
	Method	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)
3,5-Diethyl-1,2-dihydro-1-phenyl-2-propylpyridine 34562-31-7	Result	not readily biodegradable.
	Route of application	aerobic
	Degradability	> 0 - < 60 %
	Method	OECD 301 A - F

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Result	readily biodegradable
	Route of application	aerobic
	Degradability	98 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
propane 74-98-6	Result	readily biodegradable
	Route of application	aerobic
	Degradability	> 60 %
	Method	OECD 301 A - F
butane 106-97-8	Result	readily biodegradable
	Route of application	aerobic
	Degradability	> 60 %
	Method	OECD 301 A - F

Bioaccumulative potential / Mobility in soil:

acetone 67-64-1	LogPow	-0.24
	Temperature	
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
3,5-Diethyl-1,2-dihydro-1-phenyl-2-propylpyridine 34562-31-7	LogPow	6.578
	Temperature	
	Method	QSAR (Quantitative Structure Activity Relationship)
butane 106-97-8	LogPow	2.31
	Temperature	20 °C
	Method	other (measured)

Section 13. Disposal considerations

Product

Method of disposal:
Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages:
Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Class:	2
Packing group:	
Classification code:	5F
Hazard ident. number:	
UN no.:	1950
Label:	2.1
Technical name:	AEROSOLS

Railroad transport RID:

Class:	2
Packing group:	
Classification code:	5F
Hazard ident. number:	23
UN no.:	1950
Label:	2.1
Technical name:	AEROSOLS

Inland water transport ADN:

Class:	2
Packing group:	
Classification code:	5F
Hazard ident. number:	
UN no.:	1950
Label:	2.1
Technical name:	AEROSOLS

Marine transport IMDG:

Class:	2.1
Packing group:	
UN no.:	1950
Label:	2.1
EmS:	F-D ,S-U
Seawater pollutant:	Marine pollutant
Proper shipping name:	AEROSOLS (n-Heptane,3,5-Diethyl-1,2-dihydro-1-phenyl-2-propylpyridine)

Air transport IATA:

Class:	2.1
Packing group:	
Packaging instructions (passenger):	203
Packaging instructions (cargo):	203
UN no.:	1950
Label:	2.1
Proper shipping name:	Aerosols, flammable

Section 15. Regulatory information

Regulatory Information:
Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
KECI (KR)	yes
ISHL (JP)	yes
IECSC	yes
AIIC	yes
TCSI	yes
PICCS (PH)	yes
EINECS	yes

Section 16. Other information

Disclaimer:
This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.
This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).