# Safety Data Sheet



LOCTITE SF 7701 CAN1GALEN

SDS No. : 153658
V001.10
Revision: 12.01.2025
printing date: 04.11.2026

## Section 1. Identification of the substance/preparation and of the company/undertaking

**Product name:**
LOCTITE SF 7701 CAN1GALEN

**Other means of identification:**
LOCTITE SF 7701 CAN1GALEN

**Product code:**
IDH2384358

**Recommended use of the chemical and restrictions on use**

**Intended use:**
Primer, containing solvents

**Manufacturer/Importer/Distributor Representative Company**

Henkel Thailand Ltd. The Offices at Centralworld,
35th Floor, 999/9 Rama 1 Rd.,
Kwang Patumwan, Khet Patumwan,
10330 Bangkok

Thailand

Phone: +66 (2209) 8000
Fax-no.: +66 (2209) 8008

**E-mail address of person responsible for Safety Data Sheet:**
ap-ua-psra.sea@henkel.com

**Emergency Telephone for Chemical Accidents:**
FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call: +662 209 8008

## Section 2. Hazards identification

**GHS Classification:**

| Hazard Class | Hazard Category | Target organ |
|---|---|---|
| Flammable liquids | Category 2 | |
| Skin corrosion/irritation | Category 2 | |
| Specific target organ toxicity - single exposure | Category 3 | Central nervous system |
| Aspiration hazard | Category 1 | |
| Acute hazards to the aquatic environment | Category 1 | |
| Chronic hazards to the aquatic environment | Category 1 | |

**GHS label elements:**

**Hazard pictogram:**



**Signal word:**
Danger

**Hazard statement:**
H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.

**Precaution:**

**Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.

**Response:**
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
P331 Do NOT induce vomiting.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P391 Collect spillage.

**Storage:**
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.

**Disposal:**
P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

## Section 3. Composition / information on ingredients

**Substance or Mixture:**
Mixture

**Declaration of hazardous chemical:**

| Hazard component CAS-No. | Content | GHS Classification |
|---|---|---|
| n-Heptane<br>142-82-5 | 60- 100 % | Flammable liquids 2<br>H225<br>Skin corrosion/irritation 2<br>H315<br>Specific target organ toxicity - single exposure 3<br>H336<br>Aspiration hazard 1<br>H304<br>Acute hazards to the aquatic environment 1<br>H400<br>Chronic hazards to the aquatic environment 1<br>H410 |
| Methylcyclohexane<br>108-87-2 | 0.1- 1 % | Flammable liquids 2<br>H225<br>Skin corrosion/irritation 2<br>H315<br>Specific target organ toxicity - single exposure 3<br>H336<br>Aspiration hazard 1<br>H304<br>Acute hazards to the aquatic environment 1<br>H400<br>Chronic hazards to the aquatic environment 1<br>H410 |
| 1,8-Diazabicyclo[5.4.0]undec-7-ene<br>6674-22-2 | 0.1- 1 % | Corrosive to metals 1<br>H290<br>Acute toxicity 3; Oral<br>H301<br>Skin corrosion/irritation 1<br>H314<br>Serious eye damage/eye irritation 1<br>H318<br>Acute hazards to the aquatic environment 3<br>H402 |

## Section 4. First aid measures

**Inhalation:**
Move to fresh air, consult doctor if complaint persists.

**Skin contact:**
Rinse with running water and soap.
Obtain medical attention if irritation persists.

**Eye contact:**
Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

**Ingestion:**
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**Indication of immediate medical attention and special treatment needed:**
Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.
Do not induce vomiting.
Seek medical attention from a specialist.

## Section 5. Fire fighting measures

**Suitable extinguishing media:**

Foam, extinguishing powder, carbon dioxide.

**Improper extinguishing media:**
High pressure waterjet

**Combustion behaviour:**
Solvent containing flammable product. In case of fire toxic gases are released.

**Specific hazards arising from the chemical:**
Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.

**Special protection equipment and precautions for firefighters:**
Wear self-contained breathing apparatus.

**Hazardous combustion products:**
Oxides of carbon, oxides of nitrogen, irritating organic vapors.

**Additional fire fighting advice:**
In case of fire, keep containers cool with water spray.

## Section 6. Accidental release measures

**Personal precautions:**
Remove sources of ignition.
Ensure adequate ventilation.
Wear protective equipment.
Avoid contact with skin and eyes.
See advice in section 8

**Environmental precautions:**
Do not empty into drains / surface water / ground water.

**Clean-up methods:**
Store in a partly filled, closed container until disposal.
For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.
Dispose of contaminated material as waste according to Section 13.

## Section 7. Handling and storage

**Handling:**
Keep away from sources of ignition - no smoking.
Vapours should be extracted to avoid inhalation.
Avoid skin and eye contact.
See advice in section 8

**Storage:**
Store in a cool, dry place.
Refer to Technical Data Sheet.

## Section 8. Exposure controls / personal protection

**Components with specific control parameters for workplace:**

| | | |
|---|---|---|
| HEPTANE, ALL ISOMERS<br>142-82-5 | **Value type** | Time Weighted Average (TWA): |
| | **ppm** | 400 |
| | **Remarks** | ACGIH |
| HEPTANE (N-HEPTANE)<br>142-82-5 | **Value type** | Time Weighted Average (TWA): |
| | **ppm** | 500 |
| | **Remarks** | TH OEL |
| HEPTANE, ALL ISOMERS<br>142-82-5 | **Value type** | Short Term Exposure Limit (STEL): |
| | **ppm** | 500 |
| | **Remarks** | ACGIH |
| METHYLCYCLOHEXANE<br>108-87-2 | **Value type** | Time Weighted Average (TWA): |
| | **ppm** | 500 |
| | **Remarks** | TH OEL |
| Methylcyclohexane<br>108-87-2 | **Value type** | Time Weighted Average (TWA): |
| | **ppm** | 100 |
| | **Remarks** | ACGIH |

**Respiratory protection:**
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

**Hand protection:**
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**
Wear protective glasses.
Protective eye equipment should conform to EN166.

**Body protection:**
Suitable protective clothing
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Engineering controls:**
Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

**General protection and hygiene measures:**
The workplace should be equipped with an emergency shower and eye-rinsing facility.

**Hygienic measures:**
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Take off contaminated clothing and wash before reuse.

## Section 9. Physical and chemical properties

| | |
|---|---|
| **Appearance:** | liquid |
| **Odor:** | Aliphatic |
| **Odor threshold (CA):** | No data available. |
| **pH:** | Not applicable, Product is non-soluble (in water). |
| **Melting point / freezing point:** | Not applicable, Product is a liquid |
| **Specific gravity:** | 0.68 |
| **Boiling point:** | 96 - 98 °C (204.8 - 208.4 °F) |
| **Flash point:** | -2 °C (28.4 °F) |
| (Tagliabue closed cup) | |
| **Evaporation rate:** | No data available. |
| **Flammability (solid, gas):** | No data available. |
| **Lower explosive limit:** | 1.1 %(V) |
| **Upper explosive limit:** | 6.7 %(V) |
| **Vapor pressure:** | 47 hPa |
| (; 20 °C (68 °F); 50 °C (122 °F)) | 188 hPa |
| **Vapor density:** | 3.45 |
| | Heavier than air. |
| **Density:** | 0.68 g/cm3 |
| **Solubility:** | Not miscible (20 °C) |
| **Partition coefficient: n-octanol/water:** | No data available. |
| **Auto ignition:** | No data available. |
| **Decomposition temperature:** | No data available. |
| **Viscosity:** | No data available. |
| **VOC content:** | 100 % |
| (2010/75/EC) | |

## Section 10. Stability and reactivity

**Reactivity/Incompatible materials:**
Strong oxidizing agents.
**Chemical stability:**
Stable under recommended storage conditions.
**Conditions to avoid:**
Heat, flames, sparks and other sources of ignition.
**Hazardous decomposition products:**
No decomposition if used according to specifications.

## Section 11. Toxicological information

| | |
|---|---|
| **Oral toxicity:** | Acute toxicity estimate (ATE) : > 2,000 mg/kg<br>Method: Calculation method |

Symptoms of Overexposure**:** ASPIRATION: Coughing, shortness of breath, nausea. Delayed effect: bronchopneumonia or pulmonary oedema
SKIN: Redness, inflammation.
Vapors may cause drowsiness and dizziness.
Prolonged or repeated contact may cause eye irritation.

**Acute oral toxicity:**

| | | |
|---|---|---|
| n-Heptane<br>142-82-5 | Value type | LD50 |
| | Value | > 5,000 mg/kg |
| | Species | rat |
| | Method | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |
| Methylcyclohexane<br>108-87-2 | Value type | LD50 |
| | Value | > 3,200 mg/kg |
| | Species | rat |
| | Method | not specified |
| 1,8-Diazabicyclo[5.4.0]undec-7-ene<br>6674-22-2 | Value type | Acute toxicity estimate (ATE) |
| | Value | 215 mg/kg |
| | Species | |
| | Method | Expert judgement |

**Acute inhalative toxicity:**

| | | |
|---|---|---|
| n-Heptane<br>142-82-5 | Value type | LC50 |
| | Value | > 29.29 mg/l |
| | Exposure time | 4 h |
| | Species | rat |
| | Method | equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity) |
| Methylcyclohexane<br>108-87-2 | Value type | LC50 |
| | Value | > 26.3 mg/l |
| | Exposure time | 1 h |
| | Species | rat |
| | Method | not specified |

**Acute dermal toxicity:**

| | | |
|---|---|---|
| n-Heptane<br>142-82-5 | Value type | LD50 |
| | Value | > 2,000 mg/kg |
| | Species | rabbit |
| | Method | equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity) |
| Methylcyclohexane<br>108-87-2 | Value type | LD50 |
| | Value | > 2,000 mg/kg |
| | Species | rabbit |
| | Method | OECD Guideline 402 (Acute Dermal Toxicity) |

**Skin corrosion/irritation:**

| | | |
|---|---|---|
| n-Heptane<br>142-82-5 | Result | irritating |
| | Exposure time | |
| | Species | rabbit |
| | Method | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Methylcyclohexane<br>108-87-2 | Result | not irritating |
| | Exposure time | 24 h |
| | Species | rabbit |
| | Method | Draize Test |

**Serious eye damage/irritation:**

| | | |
|---|---|---|
| n-Heptane<br>142-82-5 | Result | not irritating |
| | Exposure time | |
| | Species | rabbit |
| | Method | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Methylcyclohexane<br>108-87-2 | Result | not irritating |
| | Exposure time | |
| | Species | rabbit |
| | Method | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

**Respiratory or skin sensitization:**

| | | |
|---|---|---|
| n-Heptane<br>142-82-5 | Result | not sensitising |
| | Test type | Guinea pig maximisation test |
| | Species | guinea pig |
| | Method | OECD Guideline 406 (Skin Sensitisation) |
| Methylcyclohexane<br>108-87-2 | Result | not sensitising |
| | Test type | Buehler test |
| | Species | guinea pig |
| | Method | OECD Guideline 406 (Skin Sensitisation) |

**Germ cell mutagenicity:**

| | | |
|---|---|---|
| n-Heptane<br>142-82-5 | Result | negative |
| | Type of study / Route of administration | bacterial reverse mutation assay (e.g Ames test) |
| | Metabolic activation / Exposure time | with and without |
| | Method | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| n-Heptane<br>142-82-5 | Result | negative |
| | Type of study / Route of administration | in vitro mammalian chromosome aberration test |
| | Metabolic activation / Exposure time | not applicable |
| | Method | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Methylcyclohexane<br>108-87-2 | Result | negative |
| | Type of study / Route of administration | bacterial reverse mutation assay (e.g Ames test) |
| | Metabolic activation / Exposure time | with and without |
| | Method | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Methylcyclohexane<br>108-87-2 | Result | negative |
| | Type of study / Route of administration | in vitro mammalian chromosome aberration test |
| | Metabolic activation / Exposure time | with and without |
| | Method | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Methylcyclohexane<br>108-87-2 | Result | negative |
| | Type of study / Route of administration | mammalian cell gene mutation assay |
| | Metabolic activation / Exposure time | with and without |
| | Method | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |

**Repeated dose toxicity:**

| | | |
|---|---|---|
| n-Heptane<br>142-82-5 | Result | |
| | Route of application | inhalation: vapour |
| | Exposure time / Frequency of treatment | 16 weeks12 hours/day, 7 days/week |
| | Species | rat |
| | Method | |
| Methylcyclohexane<br>108-87-2 | Result | NOAEL=250 mg/kg |
| | Route of application | oral: gavage |
| | Exposure time / Frequency of treatment | 28 ddaily |
| | Species | rat |
| | Method | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |

## Section 12. Ecological information

**General ecological information:** Do not empty into drains / surface water / ground water.

**Ecotoxicity:** H410 Very toxic to aquatic life with long lasting effects.

**Toxicity:**

| | | |
|---|---|---|
| n-Heptane<br>142-82-5 | Value type | LC50 |
| | Value | > 220 - 270 mg/l |
| | Acute Toxicity Study | Fish |

| | | |
|---|---|---|
| | Exposure time | 96 h |
| | Species | Leuciscus idus |
| | Method | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| n-Heptane<br>142-82-5 | Value type | EC50 |
| | Value | 1.5 mg/l |
| | Acute Toxicity Study | Daphnia |
| | Exposure time | 48 h |
| | Species | Daphnia magna |
| | Method | other guideline: |
| Methylcyclohexane<br>108-87-2 | Value type | LC50 |
| | Value | 2.07 mg/l |
| | Acute Toxicity Study | Fish |
| | Exposure time | 96 h |
| | Species | Oryzias latipes |
| | Method | other guideline: |
| Methylcyclohexane<br>108-87-2 | Value type | EC50 |
| | Value | 0.326 mg/l |
| | Acute Toxicity Study | Daphnia |
| | Exposure time | 48 h |
| | Species | Daphnia magna |
| | Method | other guideline: |
| Methylcyclohexane<br>108-87-2 | Value type | EC50 |
| | Value | 0.134 mg/l |
| | Acute Toxicity Study | Algae |
| | Exposure time | 72 h |
| | Species | Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata) |
| | Method | other guideline: |
| | Value type | NOEC |
| | Value | 0.022 mg/l |
| | Acute Toxicity Study | Algae |
| | Exposure time | 72 h |
| | Species | Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata) |
| | Method | other guideline: |
| 1,8-Diazabicyclo[5.4.0]undec-7-ene<br>6674-22-2 | Value type | LC50 |
| | Value | > 100 - 220 mg/l |
| | Acute Toxicity Study | Fish |
| | Exposure time | 96 h |
| | Species | Leuciscus idus |
| | Method | DIN 38412-15 |
| 1,8-Diazabicyclo[5.4.0]undec-7-ene<br>6674-22-2 | Value type | EC50 |
| | Value | 50 mg/l |
| | Acute Toxicity Study | Daphnia |
| | Exposure time | 48 h |
| | Species | Daphnia magna |
| | Method | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| 1,8-Diazabicyclo[5.4.0]undec-7-ene<br>6674-22-2 | Value type | EC50 |
| | Value | > 100 mg/l |
| | Acute Toxicity Study | Algae |
| | Exposure time | 72 h |
| | Species | Desmodesmus subspicatus (reported as Scenedesmus subspicatus) |
| | Method | EU Method C.3 (Algal Inhibition test) |
| | Value type | NOEC |
| | Value | > 100 mg/l |
| | Acute Toxicity Study | Algae |
| | Exposure time | 72 h |
| | Species | Desmodesmus subspicatus (reported as Scenedesmus subspicatus) |
| | Method | EU Method C.3 (Algal Inhibition test) |
| 1,8-Diazabicyclo[5.4.0]undec-7-ene<br>6674-22-2 | Value type | EC 50 |
| | Value | 330 mg/l |
| | Acute Toxicity Study | Bacteria |
| | Exposure time | 17 h |
| | Species | |
| | Method | not specified |

**Persistence and degradability:**

| | | |
|---|---|---|
| n-Heptane<br>142-82-5 | Result | readily biodegradable |
| | Route of application | aerobic |
| | Degradability | 70 % |

| | | |
|---|---|---|
| | Method | other guideline: |
| Methylcyclohexane<br>108-87-2 | Result | not readily biodegradable. |
| | Route of application | aerobic |
| | Degradability | 0 % |
| | Method | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| 1,8-Diazabicyclo[5.4.0]undec-7-ene<br>6674-22-2 | Result | not inherently biodegradable |
| | Route of application | aerobic |
| | Degradability | < 20 % |
| | Method | OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test) |
| | Result | not readily biodegradable. |
| | Route of application | aerobic |
| | Degradability | < 20 % |
| | Method | OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test) |

**Bioaccumulative potential / Mobility in soil:**

| | | |
|---|---|---|
| n-Heptane<br>142-82-5 | Bioconcentration factor (BCF) | 552 |
| | Exposure time | |
| | Species | calculation |
| | Temperature | |
| | Method | QSAR (Quantitative Structure Activity Relationship) |
| n-Heptane<br>142-82-5 | LogPow | 4.66 |
| | Temperature | |
| | Method | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| Methylcyclohexane<br>108-87-2 | Bioconcentration factor (BCF) | > 95 - < 321 |
| | Exposure time | 56 day |
| | Species | Cyprinus carpio |
| | Temperature | 25 °C |
| | Method | other guideline: |
| Methylcyclohexane<br>108-87-2 | LogPow | 3.88 |
| | Temperature | |
| | Method | other guideline: |
| 1,8-Diazabicyclo[5.4.0]undec-7-ene<br>6674-22-2 | Bioconcentration factor (BCF) | < 0.4 |
| | Exposure time | 42 day |
| | Species | Cyprinus carpio |
| | Temperature | |
| | Method | OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish) |

## Section 13. Disposal considerations

**Product**

**Method of disposal:**
Dispose of in accordance with local and national regulations.

**Packaging**

**Disposal of uncleaned packages:**
Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

## Section 14. Transport information

**Road transport ADR:**

| | |
|---|---|
| Class: | 3 |
| Packing group: | II |
| Classification code: | F1 |
| Hazard ident. number: | 33 |
| UN no.: | 1206 |
| Label: | 3 |
| Technical name: | HEPTANES (solution) |

**Railroad transport RID:**

| | |
|---|---|
| Class: | 3 |
| Packing group: | II |
| Classification code: | F1 |
| Hazard ident. number: | 33 |
| UN no.: | 1206 |
| Label: | 3 |
| Technical name: | HEPTANES (solution) |

**Inland water transport ADN:**

| | |
|---|---|
| Class: | 3 |
| Packing group: | II |
| Classification code: | F1 |
| Hazard ident. number: | 33 |
| UN no.: | 1206 |
| Label: | 3 |
| Technical name: | HEPTANES (solution) |

**Marine transport IMDG:**

| | |
|---|---|
| Class: | 3 |
| Packing group: | II |
| UN no.: | 1206 |
| Label: | 3 |
| EmS: | F-E ,S-D |
| Seawater pollutant: | Marine pollutant |
| Proper shipping name: | HEPTANES (solution) |

**Air transport IATA:**

| | |
|---|---|
| Class: | 3 |
| Packing group: | II |
| Packaging instructions (passenger): | 353 |
| Packaging instructions (cargo): | 364 |
| UN no.: | 1206 |
| Label: | 3 |
| Proper shipping name: | Heptanes (solution) |

## Section 15. Regulatory information

**Regulatory Information:**
Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

**Global inventory status:**

| Regulatory list | Notification |
|---|---|
| TSCA | yes |
| DSL | yes |
| KECI (KR) | yes |
| IECSC | yes |
| TCSI | yes |
| PICCS (PH) | yes |
| EINECS | yes |

## Section 16. Other information

**Disclaimer:**
This Safety Data Sheet has been generated based on Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555 only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.
This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.
Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).